## NSN 5307-00-175-1893

Locked In Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-00-175-1893 **Thread Class:** 3a nut thread **Thread Pitch Diameters:** +0.3358 to 0.3378 inches stud thread **Thread Direction:** Right-hand stud thread Thread Length: 0.560 inches nut thread **Locking Feature:** Ring, lock serrated **Overall Length:** 1.565 inches **Distance From Serrated Portion To Nut End:** 0.875 inches **Distance From Serrated Portion To Stud End:** 0.690 inches **Distance From Serrated Portion To End Of Stud Thread:** 0.080 inches **Serration Quantity:** 20 Thready Qty Per Inch (tpi): 24 nut thread **Hardness Rating:** 26.0 rockwell c **Thread Size:** 0.375 inches stud thread **Surface Finish:** 32.0 microinches nut thd **Serration Included Angle:** 102.0 degrees Material: Steel comp 4130 **Material Specification:** Mil-s-6758 military specification single material response **Surface Treatment:** 

Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Style Designator:** Locked in

**Thread Series Designator:** 

Uns stud thread

## NSN 5307-00-175-1893

Locked In Stud - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:

Shelf Life:

No

**Fiig:** A051a0

Mil-std (military Standard):

Mil-s-6758 spec.