NSN 5307-00-194-8883

Shouldered Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-00-194-8883

| View Online at https://aerobasegroup.com/nsn/5307-00-19 |
|---|
| Thread Pitch Diameters: |
| +0.7046 to 0.7086 inches stud thread |
| Thread Direction: |
| Left-hand stud thread |
| Thread Length: |
| 1.150 inches nut thread |
| Shoulder Diameter: |
| Between 1.120 inches and 1.210 inches |
| Shoulder Length: |
| Between 0.190 inches and 0.220 inches |
| Overall Length: |
| Between 3.960 inches and 4.080 inches |
| Nut End Shank Length: |
| 0.190 inches |
| Distance Across Flats: |
| Between 0.910 inches and 0.940 inches |
| Thready Qty Per Inch (tpi): |
| 16 stud thread |
| Thread Size: |
| 0.750 inches stud thread |
| Stud End Shank Length: |
| 1.545 inches |
| Stud End Shank Diameter: |
| 0.785 inches |
| Nut End Shank Diameter: |
| 0.750 inches |
| Product Name: |
| Navy special project |
| Material: |
| Steel comp 4427 |
| Material Specification: |
| Sae assn standard single material response |
| Surface Treatment: |
| Zinc |
| Surface Treatment Specification: |
| Ms 18 cl a fscm 09386 mfr ref single treatment response |
| Style Designator: |
| Shouldered |
| Thread Series Designator: |
| Uns nut thread |
| Shelf Life: |
| |

N/a

NSN 5307-00-194-8883

Shouldered Stud - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A051a0