NSN 5307-00-206-8890

Shouldered Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-00-206-8890

| Thread Class: |
|--|
| 3a stud thread |
| Thread Direction: |
| Right-hand stud thread |
| Thread Length: |
| 0.938 inches nut thread |
| Shoulder Length: |
| 0.125 inches |
| Overall Length: |
| 4.250 inches |
| Nut End Shank Length: |
| 2.626 inches |
| Distance Across Flats: |
| 0.562 inches |
| Thready Qty Per Inch (tpi): |
| 24 stud thread |
| Hardness Rating: |
| Between 26.0 rockwell c and 32.0 rockwell c |
| Thread Size: |
| 0.375 inches stud thread |
| Surface Finish: |
| 63.0 microinches stud thd |
| Nut End Shank Diameter: |
| Between 0.368 inches and 0.375 inches |
| Special Features: |
| Two holes 0.070 diameter at 90 degrees 0.125 in. From stud end |
| Material: |
| Steel |
| Material Specification: |
| Ems 85010 fscm 73342 mfr ref single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Ams 2400 assn standard single treatment response |
| Style Designator: |
| Shouldered |
| Thread Series Designator: |
| Unf stud thread |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5307-00-206-8890

Shouldered Stud - Page 2 of 2



Demilitarization:

No

Fiig:

A051a0