

View Online at <https://aerobasegroup.com/nsn/5307-00-232-0794>

**Thread Class:**

3a nut thread

**Thread Pitch Diameters:**

+0.2778/+0.2795 inches stud thread

**Thread Direction:**

Right-hand stud thread

**Thread Length:**

0.375 inches stud thread and 0.405 inches stud thread

**Locking Feature:**

Ring, lock serrated

**Overall Length:**

Between 1.655 inches and 1.715 inches

**Distance From Serrated Portion To Nut End:**

Between 1.110 inches and 1.140 inches

**Distance From Serrated Portion To Stud End:**

Between 0.545 inches and 0.575 inches

**Distance From Serrated Portion To End Of Stud Thread:**

Between 0.140 inches and 0.200 inches

**Serration Quantity:**

17

**Thready Qty Per Inch (tpi):**

28 nut thread

**Hardness Rating:**

26.0 rockwell c

**Thread Size:**

0.312 inches stud thread

**Surface Finish:**

32.0 microinches nut thd

**Serration Included Angle:**

86.0 degrees

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Style Designator:**

Locked in

**Thread Series Designator:**

Uns stud thread

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A051a0

**Mil-std (military Standard):**

Mil-s-6758 spec.