## NSN 5307-00-274-6933

Shouldered And Stepped Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-00-274-6933 **Thread Class:** 3a stud thread **Thread Direction:** Right-hand stud thread Thread Length: 0.530 inches nut thread **Shoulder Diameter:** 0.750 inches **Shoulder Length:** 0.261 inches **Overall Length:** 2.680 inches **Nut End Shank Length:** 0.389 inches **Distance From Cotter Pin Hole Centerline To Nut End:** 0.154 inches first hole **Cotter Pin Hole Diameter:** 0.085 inches second hole **Distance Across Flats:** 0.625 inches Thready Qty Per Inch (tpi): 24 stud thread **Thread Size:** 0.375 inches stud thread **Surface Finish:** 125.0 microinches **Nut End Shank Diameter:** Between 0.240 inches and 0.375 inches **Product Name:** Navy special project **Special Features:** Cotter pin hole centerline to stud end distance 0.159, 0.108 in. Min, 0.113 in. Dia Material: Steel comp e4340 **Material Specification:** Mil-s-5000 military specification all material responses **Style Designator:** Shouldered and stepped **Thread Series Designator:** Unf stud thread

N/a

Shelf Life:

## NSN 5307-00-274-6933

Shouldered And Stepped Stud - Page 2 of 2



ι	Jn	it	Of	Measure:	•

--

Demilitarization:

No

Fiig:

A051a0

Mil-std (military Standard):

Mil-s-5000 spec.