

View Online at https://aerobasegroup.com/nsn/5307-00-307-2334

NSN 5307-00-307-2334 Plain Stud - Page 1 of 1 **Thread Class:** 3a nut thread **Thread Pitch Diameters:** +0.2218/+0.2233 inches stud thread Thread Direction: Right-hand stud thread **Thread Length:** 0.813 inches nut thread and 0.884 inches nut thread **Overall Length:** Between 1.677 inches and 1.697 inches **Features Provided:** Casehardened Thready Qty Per Inch (tpi): 28 nut thread Hardness Rating: Between 36.0 rockwell c and 43.0 rockwell c **Thread Size:** 0.250 inches stud thread Surface Finish: 63.0 microinches shank **Special Features:** 160000 psi min tensile Material: Steel comp 4140 or steel comp 8740 **Material Specification:** Mil-s-5626 cond c military specification 1st material response or mil-c-6049 cond c military specification 2nd material response or ams 6382 assn standard 1st material response or ams 6322 assn standard 1st material response Surface Treatment: Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Uns stud thread Shelf Life: N/a Unit Of Measure: --**Demilitarization:**

No

Fiig:

A051a0

Mil-std (military Standard):

Mil-s-5626 spec.