## NSN 5307-00-338-5257

Shouldered And Stepped Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-00-338-5257 **Thread Class:** 3a stud thread **Thread Direction:** Right-hand stud thread Thread Length: 0.470 inches stud thread **Shoulder Length:** 0.230 inches **Overall Length:** 3.761 inches **Nut End Shank Length:** 1.321 inches **Distance From Cotter Pin Hole Centerline To Nut End:** 0.200 inches first hole and 0.672 inches first hole and 3.558 inches first hole **Cotter Pin Hole Diameter:** 0.068 inches first hole and 0.073 inches first hole **Distance Across Flats:** 0.625 inches Thready Qty Per Inch (tpi): 32 nut thread **Thread Size:** 0.312 inches stud thread **Stud End Shank Diameter:** 0.186 inches **Surface Finish:** 63.0 microinches **Nut End Shank Diameter:** 0.312 inches Material: Steel comp 8630 **Material Specification:** Mil-s-6050 military specification single material response **Surface Treatment:** Cadmium and chromate **Thread Series Designator:** Unf stud thread Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5307-00-338-5257

Shouldered And Stepped Stud - Page 2 of 2



Fiig:

A051a0

Mil-std (military Standard):

Mil-s-6050 spec.