NSN 5307-00-446-4127

Shouldered Stud - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5307-00-446-4127

| Thread Class: |
|---|
| 2a stud thread |
| Thread Direction: |
| Right-hand stud thread |
| Thread Length: |
| $0.320 \ \text{inches} \ \text{nut thread}$ and $0.330 \ \text{inches} \ \text{nut thread}$ |
| Shoulder Length: |
| Between 0.700 inches and 0.740 inches |
| Overall Length: |
| Between 1.400 inches and 1.440 inches |
| Nut End Shank Length: |
| 0.055 inches |
| Distance Across Flats: |
| Between 0.300 inches and 0.340 inches |
| Thready Qty Per Inch (tpi): |
| 32 stud thread |
| Thread Size: |
| 0.138 inches nut thread |
| Stud End Shank Length: |
| 0.040 inches |
| Stud End Shank Diameter: |
| 0.163 inches |
| Nut End Shank Diameter: |
| 0.220 inches |
| Material: |
| Steel comp 303 |
| Material Specification: |
| Qq-s-763 federal specification single material response |
| Surface Treatment: |
| Passivate |
| Style Designator: |
| Shouldered |
| Thread Series Designator: |
| Unc stud thread |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| |

A051a0

material response