## NSN 5307-00-480-1033

Shouldered And Stepped Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-00-480-1033

**Thread Class:** 

3a stud thread

**Thread Direction:** 

Right-hand stud thread

Thread Length:

1.062 inches stud thread

Shoulder Diameter:

Between 0.839 inches and 0.849 inches

**Shoulder Length:** 

Between 0.083 inches and 0.093 inches

**Overall Length:** 

Between 2.171 inches and 2.242 inches

**Nut End Shank Length:** 

Between 0.391 inches and 0.422 inches

Thready Qty Per Inch (tpi):

20 nut thread

**Hardness Rating:** 

Between 35.0 rockwell c and 40.0 rockwell c

**Thread Size:** 

0.438 inches nut thread

Stud End Shank Length:

0.017 inches

**Stud End Shank Diameter:** 

Between 0.365 inches and 0.370 inches

**Surface Finish:** 

125.0 microinches

**Nut End Shank Diameter:** 

Between 0.365 inches and 0.370 inches

Material:

Steel comp 4140

**Material Specification:** 

Ams6382 assn standard single material response

**Surface Treatment:** 

Cadmium

**Surface Treatment Specification:** 

Ams 2400 assn standard single treatment response

Style Designator:

Shouldered and stepped

**Thread Series Designator:** 

Unf nut thread

Shelf Life:

N/a

## NSN 5307-00-480-1033

Shouldered And Stepped Stud - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A051a0