NSN 5307-00-515-6700

Shouldered And Stepped Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-00-515-6700 **Thread Class:** 3a stud thread **Thread Direction:** Right-hand stud thread Thread Length: 0.540 inches nut thread Shoulder Diameter: Between 0.455 inches and 0.465 inches **Shoulder Length:** Between 0.235 inches and 0.245 inches **Overall Length:** Between 1.180 inches and 1.200 inches **Distance From Cotter Pin Hole Centerline To Nut End:** 0.100 inches first hole and 0.120 inches first hole **Cotter Pin Hole Diameter:** 0.065 inches first hole and 0.072 inches first hole Thready Qty Per Inch (tpi): 24 stud thread **Hardness Rating:** Between 30.0 rockwell c and 38.0 rockwell c **Thread Size:** 0.375 inches stud thread Stud End Shank Length: 0.082 inches **Nut End Shank Diameter:** 0.310 inches Material: Steel comp 8740 **Material Specification:** Ams 6322 assn standard single material response **Surface Treatment:** Cadmium **Style Designator:** Shouldered and stepped **Thread Series Designator:** Unf stud thread Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5307-00-515-6700

Shouldered And Stepped Stud - Page 2 of 2



Fiig:

A051a0