## NSN 5307-00-516-6482

Shouldered Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-00-516-6482

| Thread Class:   |
|---|
| 2a stud thread  |
| Thread Direction:   |
| Right-hand stud thread  |
| Thread Length:  |
| 1.620 inches nut thread   |
| Shoulder Length:  |
| Between 0.182 inches and 0.192 inches   |
| Overall Length:   |
| Between 3.360 inches and 3.400 inches   |
| Nut End Shank Length:   |
| Between 0.188 inches and 0.198 inches   |
| Distance Across Flats:  |
| 0.938 inches  |
| Thready Qty Per Inch (tpi):   |
| 11 nut thread   |
| Hardness Rating:  |
| Between 32.0 rockwell c and 38.0 rockwell c   |
| Thread Size:  |
| 0.625 inches nut thread   |
| Stud End Shank Length:  |
| 0.245 inches  |
| Stud End Shank Diameter:  |
| 0.625 inches  |
| Surface Finish:   |
| 250.0 microinches   |
| Nut End Shank Diameter:   |
| 0.625 inches  |
| Material:   |
| Steel comp 416  |
| Material Specification:   |
| Aisi assn standard single material response or astm a582 assn standard single material response |
| Surface Treatment:  |
| Passivate   |
| Style Designator:   |
| Shouldered  |
| Thread Series Designator:   |
| Unc nut thread  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |

## NSN 5307-00-516-6482

Shouldered Stud - Page 2 of 2

Demilitarization:

No

Fiig:

A051a0

