NSN 5307-00-564-6224

Locked In Stud - Page 1 of 2



6224

View Online at https://aerobasegroup.com/nsn/5307-00-564-6 Thread Class: 3a nut thread Thread Pitch Diameters: +0.3926/+0.3946 inches stud thread Thread Direction: Right-hand stud thread Thread Length: 0.625 inches nut thread Locking Feature: Ring, lock serrated Overall Length: 2.250 inches Distance From Serrated Portion To Nut End: 1.500 inches Distance From Serrated Portion To Stud End: 0.750 inches Distance From Serrated Portion To End Of Stud Thread: 0.750 inches Distance From Serrated Portion To End Of Stud Thread: 0.232 inches Distance From Serrated Portion To End Of Stud Thread: 0.172 inches first hole Cotter Pin Hole Diameter: 0.106 inches first hole Thread Size: 0.438 inches stud thread Material: Steel comp 4130 Material Specification: Mil-s-6758 military specification single material response Surface Treatment: Cadmium Style Designator: Locked in Thread Series Designator: Uns stud thread Sheff Life: N/a
3a nut thread Thread Pitch Diameters: 10.3926/+0.3946 inches stud thread Thread Direction: Right-hand stud thread Thread Length: 0.625 inches nut thread Locking Feature: Ring, lock serrated Overall Length: 2.250 inches Distance From Serrated Portion To Nut End: 1.500 inches Distance From Serrated Portion To Stud End: 0.750 inches Distance From Serrated Portion To End Of Stud Thread: 0.232 inches Distance From Serrated Portion To End Of Stud Thread: 0.232 inches Distance From Cotter Pin Hole Centerline To Nut End: 0.172 inches first hole Chready Qty Per Inch (tpi): 24 nut thread Thread Size: 0.438 inches stud thread Material: Stel comp 4130 Material Specification: Mil-s-6758 military specification single material response Surface Treatment: Locked in Thread Series Designator: Ions stud thread Stife Life:
Thread Pitch Diameters:+0.3926/+0.3946 inches stud threadThread Direction:Right-hand stud threadThread Length:0.625 inches nut threadLocking Feature:Ring, lock serratedOverall Length:2.250 inchesDistance From Serrated Portion To Nut End:1.500 inchesDistance From Serrated Portion To Stud End:0.750 inchesDistance From Serrated Portion To Stud End:0.232 inchesDistance From Serrated Portion To End Of Stud Thread:0.172 inchesDistance From Serrated Portion To End Of Stud Thread:0.102 inchesDistance From Serrated Portion To End Of Stud Thread:0.172 inchesDistance From Serrated Portion To End Of Stud Thread:0.102 inchesDistance From Serrated Portion To End Of Stud Thread:0.102 inchesDistance From Serrated Portion To End Of Stud Thread:0.102 inchesDistance From Cotter Pin Hole Centerline To Nut End:0.102 inches first holeThready Qty Per Inch (tpi):24 nut threadMaterial:Steel comp 4130Material Specification:Mil-s-6758 military specification single material responseSurface Treatment:CadmiumStyle Designator:Locked inThread Series Designator:Uns stud threadShelf Life:
 +0.3926/+0.3946 inches stud thread Thread Direction: Right-hand stud thread Thread Length: 0.625 inches nut thread Locking Feature: Ring, lock serrated Overall Length: 2.250 inches Distance From Serrated Portion To Nut End: 1.500 inches Distance From Serrated Portion To Stud End: 0.750 inches Distance From Serrated Portion To Stud End: 0.750 inches Distance From Serrated Portion To Stud End: 0.750 inches Distance From Serrated Portion To Stud End: 0.172 inches first hole Cotter Pin Hole Diameter: 0.106 inches first hole Thready Qty Per Inch (tpi): 24 nut thread Material: Steel comp 4130 Material Specification: Mil-s-6758 military specification single material response Surface Treatment: Locked in Thread Series Designator: Uns stud thread Shelf Life:
Thread Direction:Right-hand stud threadRight-hand stud threadDread Length:0.625 inches nut threadLocking Feature:Ring, lock serratedOverall Length:2.250 inchesDistance From Serrated Portion To Nut End:1.500 inchesDistance From Serrated Portion To Stud End:0.750 inchesDistance From Serrated Portion To End Of Stud Thread:0.232 inchesDistance From Serrated Portion To End Of Stud Thread:0.172 inchesDistance From Cotter Pin Hole Centerline To Nut End:0.172 inches first holeCotter Pin Hole Diameter:0.106 inches first holeThready Qty Per Inch (tpi):24 nut threadHaterial:Steel comp 4130Material Specification:Mil-s-6758 military specification single material responseSurface Treatment:CadmiumStyle Designator:Locked inThread Series Designator:Uns stud threadShelf Life:
Right-hand stud threadInread Length:0.625 inches nut threadLocking Feature:Ring, lock serratedOverall Length:2.250 inchesDistance From Serrated Portion To Nut End:1.500 inchesDistance From Serrated Portion To Stud End:0.750 inchesDistance From Serrated Portion To End Of Stud Thread:0.232 inchesDistance From Cotter Pin Hole Centerline To Nut End:0.172 inches first holeCotter Pin Hole Diameter:0.106 inches first holeThready Qty Per Inch (tpi):24 nut threadHareial:0.438 inches stud threadMaterial:Steel comp 4130Material SpecificationMil-s-6758 military specification single material responseSurface Treatment:CadmiumStyle Designator:Locked inThread Series Designator:Uns stud threadShelf Life:
Thread Length:0.625 inches nut threadLocking Feature:Ring, lock serratedOverall Length:2.250 inchesDistance From Serrated Portion To Nut End:1.500 inchesDistance From Serrated Portion To Stud End:0.750 inchesDistance From Serrated Portion To End Of Stud Thread0.232 inchesDistance From Cotter Pin Hole Centerline To Nut End:0.172 inches first holeCotter Pin Hole Diameter:0.106 inches first holeThready Qty Per Inch (tpi):24 nut threadThread Size:0.438 inches stud threadMaterial:Steel comp 4130Material Specification single material responseSurface Treatment:CadmiumStyle Designator:Locked inThread Series Designator:Uns stud threadShelf Life:
0.625 inches nut thread Locking Feature: Ring, lock serrated Overall Length: 2.250 inches Distance From Serrated Portion To Nut End: 1.500 inches Distance From Serrated Portion To Stud End: 0.750 inches Distance From Serrated Portion To End Of Stud Thread O.232 inches Distance From Cotter Pin Hole Centerline To Nut End: 0.232 inches Distance From Cotter Pin Hole Centerline To Nut End: 0.172 inches first hole Cotter Pin Hole Diameter: 0.106 inches first hole Thread Qty Per Inch (tpi): 24 nut thread Thread Size: 0.438 inches stud thread Material: Steel comp 4130 Material Specification single material response Surface Treatment: Cadmium Style Designator: Locked in Thread Series Designator: Uns stud thread
Locking Feature:Ring, lock serratedOverall Length:2.250 inchesDistance From Serrated Portion To Nut End:1.500 inchesDistance From Serrated Portion To Stud End:0.750 inchesDistance From Serrated Portion To End Of Stud Thread:0.232 inchesDistance From Cotter Pin Hole Centerline To Nut End:0.172 inches first holeCotter Pin Hole Diameter:0.106 inches first holeThread Size:0.438 inches stud threadMaterial:Steel comp 4130Material Specification:CadmiumStyle Designator:CadmiumStyle Designator:Locked inThread Size:Dustance Treatment:CadmiumStyle Designator:Locked inThread Size:Dustance Treatment:CadmiumStyle Designator:Locked inThread Size:Dustance Treatment:CadmiumStyle Designator:Locked inThread Size:Dustud threadStyle Designator:Locked inStyle Designator:Locked inStyle Designator:Locked inStyle Life:Distance Treatment:Dustud threadDistance Treatment:Dustud threadDistance Treatment:Dustud threadDistance Treatment:Dustud threadDistance Treatment:Dustud threadDustud thread
Ring, lock serratedOverall Length:2.250 inchesDistance From Serrated Portion To Nut End:1.500 inchesDistance From Serrated Portion To Stud End:0.750 inchesDistance From Serrated Portion To End Of Stud Thread:0.232 inchesDistance From Cotter Pin Hole Centerline To Nut End:0.172 inches first holeCotter Pin Hole Diameter:0.106 inches first holeThready Qty Per Inch (tpi):24 nut threadThread Size:0.438 inches stud threadMaterial:Steel comp 4130Material Specification:CadmiumStyle Designator:Locked inThread Series Designator:Uns stud threadHireadStuff Life:
Overall Length:2.250 inchesDistance From Serrated Portion To Nut End:1.500 inchesDistance From Serrated Portion To Stud End:0.750 inchesDistance From Serrated Portion To End Of Stud Thread:0.232 inchesDistance From Cotter Pin Hole Centerline To Nut End:0.172 inches first holeCotter Pin Hole Diameter:0.106 inches first holeThready Qty Per Inch (tpi):24 nut threadThread Size:0.438 inches stud threadMaterial:Steel comp 4130Material Specification single material responseSurface Treatment:CadmiumStyle Designator:Locked inThread Series Designator:Uns stud threadShelf Life:
2.250 inches Distance From Serrated Portion To Nut End: 1.500 inches Distance From Serrated Portion To Stud End: 0.750 inches Distance From Serrated Portion To End Of Stud Thread: 0.232 inches Distance From Cotter Pin Hole Centerline To Nut End: 0.172 inches first hole Cotter Pin Hole Diameter: 0.106 inches first hole Thready Qty Per Inch (tpi): 24 nut thread Thread Size: 0.438 inches stud thread Material: Steel comp 4130 Material Specification single material response Surface Treatment: Cadmium Style Designator: Locked in Thread Series Designator: Uns stud thread Shelf Life:
Distance From Serrated Portion To Nut End:1.500 inchesDistance From Serrated Portion To Stud End:0.750 inchesDistance From Serrated Portion To End Of Stud Thread:0.232 inchesDistance From Cotter Pin Hole Centerline To Nut End:0.172 inches first holeCotter Pin Hole Diameter:0.106 inches first holeThready Qty Per Inch (tpi):24 nut threadThread Size:0.438 inches stud threadMaterial:Steel comp 4130Material SpecificationMil-s-6758 military specification single material responseSurface Treatment:CadmiumStyle Designator:Locked inThread Size:Uns stud threadStyle Designator:Locked inStyle Designator:Locked inMin-s 6758 military specification single material responseStyle Designator:Locked inChread Series Designator:Locked inChread Series Designator:Locked inChread Series Designator:Locked inChread Series Designator:Chread Serie
 1.500 inches Distance From Serrated Portion To Stud End: 0.750 inches Distance From Serrated Portion To End Of Stud Thread: 0.232 inches Distance From Cotter Pin Hole Centerline To Nut End: 0.172 inches first hole Cotter Pin Hole Diameter: 0.106 inches first hole Thready Qty Per Inch (tpi): 24 nut thread Thread Size: 0.438 inches stud thread Material: Steel comp 4130 Material Specification: Mil-s-6758 military specification single material response Surface Treatment: Cadmium Style Designator: Locked in Thread Series Designator: Uns stud thread Shelf Life:
Distance From Serrated Portion To Stud End:0.750 inchesDistance From Serrated Portion To End Of Stud Thread:0.232 inchesDistance From Cotter Pin Hole Centerline To Nut End:0.172 inches first holeCotter Pin Hole Diameter:0.106 inches first holeThready Qty Per Inch (tpi):24 nut threadThread Size:0.438 inches stud threadMaterial:Steel comp 4130Material Specification:Mil-s-6758 military specification single material responseSurface Treatment:CadmiumStyle Designator:Locked inThread Series Designator:Uns stud threadShelf Life:
0.750 inches Distance From Serrated Portion To End Of Stud Thread: 0.232 inches Distance From Cotter Pin Hole Centerline To Nut End: 0.172 inches first hole Cotter Pin Hole Diameter: 0.106 inches first hole Thready Qty Per Inch (tpi): 24 nut thread Thread Size: 0.438 inches stud thread Material: Steel comp 4130 Material Specification: Mil-s-6758 military specification single material response Surface Treatment: Cadmium Style Designator: Locked in Thread Series Designator: Uns stud thread Shelf Life:
Distance From Serrated Portion To End Of Stud Thread: 0.232 inches Distance From Cotter Pin Hole Centerline To Nut End: 0.172 inches first hole Cotter Pin Hole Diameter: 0.106 inches first hole Thready Qty Per Inch (tpi): 24 nut thread Thread Size: 0.438 inches stud thread Material: Steel comp 4130 Material Specification: Mil-s-6758 military specification single material response Surface Treatment: Cadmium Style Designator: Locked in Thread Series Designator: Uns stud thread
0.232 inches Distance From Cotter Pin Hole Centerline To Nut End: 0.172 inches first hole Cotter Pin Hole Diameter: 0.106 inches first hole Thready Qty Per Inch (tpi): 24 nut thread Thread Size: 0.438 inches stud thread Material: Steel comp 4130 Material Specification: Mil-s-6758 military specification single material response Surface Treatment: Cadmium Style Designator: Locked in Thread Series Designator: Uns stud thread Shelf Life:
 Distance From Cotter Pin Hole Centerline To Nut End: 0.172 inches first hole Cotter Pin Hole Diameter: 0.106 inches first hole Thready Qty Per Inch (tpi): 24 nut thread Thread Size: 0.438 inches stud thread Material: Steel comp 4130 Material Specification: Mil-s-6758 military specification single material response Surface Treatment: Cadmium Style Designator: Locked in Thread Series Designator: Uns stud thread Shelf Life:
0.172 inches first hole Cotter Pin Hole Diameter: 0.106 inches first hole Thready Qty Per Inch (tpi): 24 nut thread Thread Size: 0.438 inches stud thread Material: Steel comp 4130 Material Specification: Mil-s-6758 military specification single material response Surface Treatment: Cadmium Style Designator: Locked in Thread Series Designator: Uns stud thread Shelf Life:
Cotter Pin Hole Diameter: 0.106 inches first hole Thready Qty Per Inch (tpi): 24 nut thread Thread Size: 0.438 inches stud thread Material: Steel comp 4130 Material Specification: Mil-s-6758 military specification single material response Surface Treatment: Cadmium Style Designator: Locked in Thread Series Designator: Uns stud thread Shelf Life:
0.106 inches first hole Thready Qty Per Inch (tpi): 24 nut thread Thread Size: 0.438 inches stud thread Material: Steel comp 4130 Material Specification: Mil-s-6758 military specification single material response Surface Treatment: Cadmium Style Designator: Locked in Thread Series Designator: Uns stud thread Shelf Life:
Thready Qty Per Inch (tpi): 24 nut thread Thread Size: 0.438 inches stud thread Material: Steel comp 4130 Material Specification: Mil-s-6758 military specification single material response Surface Treatment: Cadmium Style Designator: Locked in Thread Series Designator: Uns stud thread Shelf Life:
24 nut thread Thread Size: 0.438 inches stud thread Material: Steel comp 4130 Material Specification: Mil-s-6758 military specification single material response Surface Treatment: Cadmium Style Designator: Locked in Thread Series Designator: Uns stud thread Shelf Life:
Thread Size:0.438 inches stud threadMaterial:Steel comp 4130Material Specification:Mil-s-6758 military specification single material responseSurface Treatment:CadmiumStyle Designator:Locked inThread Series Designator:Uns stud threadShelf Life:
0.438 inches stud thread Material: Steel comp 4130 Material Specification: Mil-s-6758 military specification single material response Surface Treatment: Cadmium Style Designator: Locked in Thread Series Designator: Uns stud thread Shelf Life:
Material:Steel comp 4130Material Specification:Mil-s-6758 military specification single material responseSurface Treatment:CadmiumStyle Designator:Locked inThread Series Designator:Uns stud threadShelf Life:
Steel comp 4130 Material Specification: Mil-s-6758 military specification single material response Surface Treatment: Cadmium Style Designator: Locked in Thread Series Designator: Uns stud thread Shelf Life:
Material Specification: Mil-s-6758 military specification single material response Surface Treatment: Cadmium Style Designator: Locked in Thread Series Designator: Uns stud thread Shelf Life:
Mil-s-6758 military specification single material response Surface Treatment: Cadmium Style Designator: Locked in Thread Series Designator: Uns stud thread Shelf Life:
Surface Treatment: Cadmium Style Designator: Locked in Thread Series Designator: Uns stud thread Shelf Life:
Cadmium Style Designator: Locked in Thread Series Designator: Uns stud thread Shelf Life:
Style Designator: Locked in Thread Series Designator: Uns stud thread Shelf Life:
Locked in Thread Series Designator: Uns stud thread Shelf Life:
Thread Series Designator: Uns stud thread Shelf Life:
Uns stud thread Shelf Life:
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5307-00-564-6224

Locked In Stud - Page 2 of 2

Fiig: A051a0

Mil-std (military Standard):

Mil-s-6758 spec.

