NSN 5307-00-566-3227

Shouldered And Stepped Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-00-566-3227 **Thread Class:** 3a stud thread **Thread Direction:** Right-hand stud thread Thread Length: 2.000 inches stud thread **Shoulder Length:** 0.375 inches **Overall Length:** 3.781 inches **Nut End Shank Length:** Between 0.698 inches and 0.703 inches **Distance From Cotter Pin Hole Centerline To Nut End:** 0.125 inches first hole **Cotter Pin Hole Diameter:** 0.106 inches first hole **Distance Across Flats:** 0.750 inches Thready Qty Per Inch (tpi): 20 nut thread Hardness Rating: Between 34.0 rockwell c and 38.0 rockwell c **Thread Size:** 0.625 inches stud thread **Nut End Shank Diameter:** Between 0.432 inches and 0.434 inches Material: Steel comp 4130 **Material Specification:** Mil-s-6758, cond c military specification single material response **Surface Treatment:** Chromium and cadmium **Style Designator:** Shouldered and stepped **Thread Series Designator:** Unf stud thread Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5307-00-566-3227

Shouldered And Stepped Stud - Page 2 of 2



Fiig:

A051a0

Mil-std (military Standard):

Mil-s-6758 spec.