

NSN 5307-00-616-2533 Stepped Stud - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5307-00-616-2533 **Thread Class:** 3a nut thread **Thread Pitch Diameters:** +0.2930/+0.2945 inches stud thread **Thread Direction:** Right-hand stud thread Thread Length: 0.615 inches stud thread and 0.635 inches stud thread **Shank Diameter:** Between 0.221 inches and 0.231 inches **Overall Length:** Between 1.240 inches and 1.260 inches **Distance From Cotter Pin Hole Centerline To Nut End:** 0.100 inches first hole and 0.120 inches first hole **Cotter Pin Hole Diameter:** 0.065 inches first hole and 0.072 inches first hole Thready Qty Per Inch (tpi): 28 nut thread

Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

**Thread Size:** 

0.312 inches stud thread

Surface Finish:

63.0 microinches shank

Material:

Steel comp 8740

**Material Specification:** 

Ams 6322 assn standard single material response

**Surface Treatment:** 

Cadmium

**Surface Treatment Specification:** 

Ams 2400 assn standard single treatment response

**Style Designator:** 

Stepped

**Thread Series Designator:** 

Uns stud thread

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

## **NSN 5307-00-616-2533** Stepped Stud - Page 2 of 2



Fiig:

A051a0