NSN 5307-00-637-1084

Shouldered Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-00-637-1084

Thread Pitch Diameters:
+0.7044/+0.7084 inches stud thread
Thread Direction:
Left-hand stud thread
Thread Length:
1.218 inches nut thread
Shoulder Diameter:
Between 1.120 inches and 1.210 inches
Shoulder Length:
Between 0.190 inches and 0.220 inches
Overall Length:
Between 3.710 inches and 3.830 inches
Nut End Shank Length:
Between 1.030 inches and 1.060 inches
End Application:
E-3a awacs; semi trailer (m870); 12-ton semi trailer
Distance Across Flats:
Between 0.910 inches and 0.940 inches
Thready Qty Per Inch (tpi):
16 stud thread
Hardness Rating:
Between 18.0 rockwell c and 28.0 rockwell c
Thread Size:
0.750 inches stud thread
Stud End Shank Length:
0.302 inches
Stud End Shank Diameter:
Between 0.910 inches and 0.940 inches
Nut End Shank Diameter:
Between 0.783 inches and 0.786 inches
Special Features:
0.125 in. Radius between wrench flat shoulder and nut end
Material:
Steel
Style Designator:
Shouldered
Thread Series Designator:
Uns nut thread
Shelf Life:
N/a
Unit Of Measure:

NSN 5307-00-637-1084

Shouldered Stud - Page 2 of 2

Demilitarization:

No

Fiig:

A051a0

