NSN 5307-00-637-5218

Plain Stud - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5307-00-637-5218

| Thread Class: |
|--|
| 3a nut thread |
| Thread Pitch Diameters: |
| +0.2248/+0.2263 inches stud thread |
| Thread Direction: |
| Right-hand stud thread |
| Thread Length: |
| 0.438 inches nut thread |
| Overall Length: |
| Between 1.115 inches and 1.135 inches |
| Distance From Cotter Pin Hole Centerline To Nut End: |
| 0.110 inches first hole |
| Cotter Pin Hole Diameter: |
| 0.065 inches first hole and 0.072 inches first hole |
| Thready Qty Per Inch (tpi): |
| 28 nut thread |
| Hardness Rating: |
| Between 26.0 rockwell c and 32.0 rockwell c |
| Thread Size: |
| 0.250 inches stud thread |
| Surface Finish: |
| 63.0 microinches shank |
| Material: |
| Steel comp 8740 |
| Material Specification: |
| Ams 6322 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Ams 2400 assn standard single treatment response |
| Thread Series Designator: |
| Uns stud thread |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A051a0 |
| |
| |