## NSN 5307-00-639-3980

Shouldered And Stepped Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-00-639-3980

**Thread Class:** 

3a nut thread

**Thread Pitch Diameters:** 

+0.4613 to 0.4628 inches stud thread

**Thread Direction:** 

Right-hand stud thread

**Thread Length:** 

0.580 inches and 0.640 inches nut thread

**Shoulder Diameter:** 

Between 0.670 inches and 0.690 inches

**Shoulder Length:** 

Between 0.050 inches and 0.070 inches

**Overall Length:** 

1.850 inches

**Nut End Shank Length:** 

Between 0.663 inches and 0.723 inches

**Features Provided:** 

Casehardened

Thready Qty Per Inch (tpi):

24 nut thread

**Hardness Rating:** 

Between 26.0 rockwell c and 32.0 rockwell c

**Thread Size:** 

0.500 inches stud thread

Stud End Shank Length:

Any acceptable

Stud End Shank Diameter:

0.426 inches

Surface Finish:

63.0 microinches shank

**Nut End Shank Diameter:** 

0.310 inches

Material:

Steel comp 8740

**Material Specification:** 

Ams 6322 assn standard single material response

**Surface Treatment:** 

Cadmium

**Surface Treatment Specification:** 

Ams 2400 assn standard single treatment response

**Style Designator:** 

Shouldered and stepped

## NSN 5307-00-639-3980

Shouldered And Stepped Stud - Page 2 of 2



		•		
Ιh	read	Series	Desiar	nator:

Uns stud thread

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A051a0