Recessed And Stepped Stud - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5307-00-678-1422

| Thread Class: | |
|--------------------|---|
| 3a stud thread | |
| Thread Direction | |
| Right-hand stud th | hread |
| Thread Length: | |
| 0.680 inches stud | d thread |
| Overall Length: | |
| 4.060 inches | |
| Plain Shank Diar | neter: |
| Between 0.4258 i | nches and 0.4375 inches |
| Length Of Reces | sed Portion Of Shank: |
| 0.380 inches | |
| Diameter Of Rec | essed Portion Of Shank: |
| Between 0.3042 i | nches and 0.3125 inches |
| Thready Qty Per | Inch (tpi): |
| 24 nut thread | |
| Thread Size: | |
| 0.438 inches stud | thread |
| Special Features | |
| 7/16-14unc-3a the | d, 0.760 inl lg located 1.000 in. From recessed shank end |
| Material: | |
| Steel | |
| Material Specific | ation: |
| Qq-s-631 federal | specification single material response or qq-s-634 federal specification single material response |
| Surface Treatme | nt: |
| Zinc | |
| Surface Treatme | nt Specification: |
| Qq-z-325 federal | specification single treatment response |
| Style Designator | : |
| Recessed and ste | pped |
| Thread Series De | esignator: |
| Unf nut thread | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | : |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A051a0 | |