Shouldered And Stepped Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-00-685-3284

Thread Class:         1a nut thread         Thread Pitch Diameters:         +0.4082/+0.4097 inches stud thread         Thread Direction:         Right-hand stud thread         Thread Length:         0.871 inches stud thread         Shoulder Diameter:         Between 0.548 inches and 0.552 inches         Shoulder Length:         Between 0.693 inches and 0.095 inches         Overall Length:         Between 0.093 inches and 0.095 inches         Overall Length:         Between 0.278 inches and 0.298 inches         Thread Yut Per Inch (tpi):         14 stud thread         Hardness Rating:         Between 0.278 inches and 0.298 inches         Thread Yut Per Inch (tpi):         14 stud thread         Hardness Rating:         Between 2.4.0 rockwell c and 37.0 rockwell c         Thread Shank Length:         0.437 inches stud thread         Stud End Shank Length:         0.430 inches         Stud End Shank Length:         0.300 inches         Stud End Shank Length:         0.300 inches         Stud End Shank Diameter:         0.330 inches         Material Specification:         Austand Shand Diamet		
Thread Pick Diameters:         +0.4082/+0.4097 inches stud thread         Thread Direction:         Right-hand stud thread         Thread Length:         0.871 inches stud thread         Shoulder Diameter:         Between 0.548 inches and 0.552 inches         Shoulder Length:         Between 0.093 inches and 0.095 inches         Overall Length:         Between 0.093 inches and 0.295 inches         Nut End Shank Length:         Between 0.278 inches and 0.295 inches         Thread VI Per Inch (tpi):         14 stud thread         Hardness Rating:         Between 0.278 inches and 0.700 rockwell c         Thread Size:         0.437 inches stud thread         Hardness Rating:         0.430 inches         Stud End Shank Length:         0.430 inches         Stud End Shank Length:         0.430 inches         Nut End Shank Diameter:         0.330 inches         Material Specification:         Nut End Shank Diameter:         0.330 inches         Material Specification:         Anse 5735 assn standard single material response         Strife Teatment:         Pasivate         Shouldered and stepped<	Thread Class:	
<ul> <li>b. 4082/40.4097 inches stud thread</li> <li>Thread Direction:</li> <li>Right-hand stud thread</li> <li>Thread Length:</li> <li>0.871 inches stud thread</li> <li>Shoulder Diameter:</li> <li>Between 0.548 inches and 0.552 inches</li> <li>Shoulder Length:</li> <li>Between 0.093 inches and 0.095 inches</li> <li>Overall Length:</li> <li>Between 0.278 inches and 0.095 inches</li> <li>Nut End Shank Length:</li> <li>Between 0.278 inches and 0.298 inches</li> <li>Thread Qty Per Inch (tpi):</li> <li>14 stud thread</li> <li>Hardness Rating:</li> <li>Between 2.4.0 rockwell c and 37.0 rockwell c</li> <li>Thread Size:</li> <li>0.437 inches stud thread</li> <li>Stud End Shank Length:</li> <li>0.430 inches</li> <li>Nut End Shank Length:</li> <li>0.310 inches</li> <li>Material:</li> <li>Inon alloy 660</li> <li>Material Specification:</li> <li>Ars 753 assn standard single material response</li> <li>Stufer Treatment:</li> <li>Passivate</li> <li>Style Designator:</li> <li>Shouldered and steped</li> <li>Thread Steped</li> <li>Thread Steped</li> <li>Thread Steped</li> <li>Style Designator:</li> <li>Chouler Stangta Stangta</li></ul>	1a nut thread	
Thread Direction:Right-hand stud threadThread Length:0.871 inches stud threadShoulder Diameter:Between 0.548 inches and 0.552 inchesShoulder Length:Between 0.093 inches and 0.095 inchesOverall Length:Between 2.050 inches and 2.070 inchesNut End Shank Length:Between 0.278 inches and 0.298 inchesThread Qty Per Inch (tpi):14 stud threadHardness Rating:Between 24.0 rockwell c and 37.0 rockwell cThread Size:0.437 inches stud threadStud End Shank Length:0.430 inchesStud End Shank Length:0.300 inchesStud End Shank Diameter:0.310 inchesNut End Shank Diameter:0.330 inchesStud End Shank Diameter:0.330 inchesSurface Treatment:PassivateSurface Treatment:PassivateSurface Treatment:PassivateSurface Treatment:PassivateSurface Instruction:Surface Instruction:Surface Instruction:Surface Instruction:Surface Instruction:PassivateSurface Instruction:Surface Instruction:	Thread Pitch Diameters:	
Right-hand stud thread         Thread Length:         0.871 inches stud thread         Shoulder Diameter:         Between 0.548 inches and 0.552 inches         Shoulder Length:         Between 0.093 inches and 0.095 inches         Overall Length:         Between 2.050 inches and 2.070 inches         Nut End Shank Length:         Between 0.278 inches and 0.298 inches         Thread Qty Per Inch (tpi):         14 stud thread         Hardness Rating:         Between 2.4.0 rockwell c and 37.0 rockwell c         Thread Size:         0.437 inches stud thread         Stud End Shank Length:         0.430 inches         Stud End Shank Length:         0.430 inches         Stud End Shank Diameter:         0.330 inches         Nut End Shank Diameter:         0.330 inches         Material Specification:         Ams 5735 assn standard single material response         Surface Treatment:         Passivale         Shouldered and stepped         Thread Series Designator:         Install Specification:         Nut End Shank Jameter:         Nats 735 assn standard single material response         Surface Treatment:	+0.4082/+0.4097 inches stud thread	
Tread Length:         0.871 inches stud thread         Shoulder Diameter:         Between 0.548 inches and 0.552 inches         Shoulder Length:         Between 0.093 inches and 0.095 inches         Overall Length:         Between 2.050 inches and 2.070 inches         Nut End Shank Length:         Between 0.278 inches and 0.298 inches         Thread Qty Per Inch (tpi):         14 stud thread         Hardness Rating:         Between 24.0 rockwell c and 37.0 rockwell c         Thread Size:         0.437 inches stud thread         Stud End Shank Length:         0.430 inches         Mut End Shank Length:         0.430 inches         Mut End Shank Length:         0.430 inches         Mut End Shank Length:         0.300 inches         Mut End Shank Diameter:         0.330 inches         Material Specification:         Arns 5735 assn standard single material response         Surface Treatment:         Passivate         Style Designator:         Shouldered and stepped         Thread Stepis Designator:         Uns stud thread	Thread Direction:	
0.871 inchesShoulder Diameter:Between 0.548 inches and 0.552 inchesShoulder Length:Between 0.093 inches and 0.095 inchesOverall Length:Between 2.050 inches and 2.070 inchesNut End Shank Length:Between 0.278 inches and 0.298 inchesThready Qty Per Inch (tpi):14 stud threadHardness Rating:Between 24.0 rockwell c and 37.0 rockwell cThread Size:0.437 inches stud threadStud End Shank Length:0.600 inchesStud End Shank Length:0.301 inches0.310 inchesStud End Shank Diameter:0.330 inchesMaterial Specification:Aren Str35 assn standard single material responseSurface Treatment:PassivateStyle Designator:Chread Stries Designator:Uns stud threadShelf Life:N/a	Right-hand stud thread	
Shoulder Diameter: Between 0.548 inches and 0.552 inches Shoulder Length: Between 0.093 inches and 0.095 inches Overall Length: Between 2.050 inches and 2.070 inches Nut End Shank Length: Between 0.278 inches and 0.298 inches Thready Qty Per Inch (tpi): 14 stud thread Hardness Rating: Between 24.0 rockwell c and 37.0 rockwell c Thread Size: 0.437 inches stud thread Stud End Shank Length: 0.600 inches Stud End Shank Length: 0.310 inches Nut End Shank Diameter: 0.330 inches Material: Iron alloy 660 Material Specification: Ams 5735 assn standard single material response Surface Treatment: Passivate Style Designator: Shouldered and stepped Thread Siewie Name	Thread Length:	
Between 0.548 inches and 0.552 inches Shoulder Length: Between 0.093 inches and 0.095 inches Overall Length: Between 2.050 inches and 2.070 inches Nut End Shank Length: Between 0.278 inches and 0.298 inches Thready Qty Per Inch (tpi): 14 stud thread Hardness Rating: Between 24.0 rockwell c and 37.0 rockwell c Thread Size: 0.437 inches stud thread Stud End Shank Length: 0.600 inches Stud End Shank Length: 0.310 inches Nut End Shank Diameter: 0.330 inches Material: Iron alloy 660 Material Specification: Ams 5735 assn standard single material response Surface Treatment: Passivate Style Designator: Shouldered and stepped Thread Siewie Name Siewie	0.871 inches stud thread	
Shoulder Length:         Between 0.093 inches and 0.095 inches         Overall Length:         Between 2.050 inches and 2.070 inches         Nut End Shank Length:         Between 0.278 inches and 0.298 inches         Thready Qty Per Inch (tpi):         14 stud thread         Hardness Rating:         Between 24.0 rockwell c and 37.0 rockwell c         Thread Size:         0.437 inches stud thread         Stud End Shank Length:         0.437 inches stud thread         Stud End Shank Diameter:         0.301 inches         Nut End Shank Diameter:         0.330 inches         Material:         Iron alloy 660         Material Specification:         Arns 5735 assn standard single material response         Surface Treatment:         Passivate         Style Designator:         Shouldered and stepped         Thread Series Designator:         Uns stud thread	Shoulder Diameter:	
Between 0.093 inches and 0.095 inchesOverall Length:Between 2.050 inches and 2.070 inchesNut End Shank Length:Between 0.278 inches and 0.298 inchesThready Qty Per Inch (tpi):14 stud threadHardness Rating:Between 2.0 rockwell c and 37.0 rockwell cThread Size:0.437 inches stud threadStud End Shank Length:0.437 inches stud threadStud End Shank Length:0.600 inchesStud End Shank Diameter:0.310 inchesNut End Shank Diameter:0.330 inchesMaterial:Ironaloy 660Material Specification:Arns 5735 assn standard single material responseSurface Treatment:PassivateSyle Designator:Shouldered and steppedThread Series Designator:Uns stud threadShif Life:N/a	Between 0.548 inches and 0.552 inches	
Overall Length:Between 2.050 inches and 2.070 inchesNut End Shank Length:Between 0.278 inches and 0.298 inchesThready Qty Per Inch (tpi):14 stud threadHardness Rating:Between 24.0 rockwell c and 37.0 rockwell cThread Size:0.437 inches stud threadStud End Shank Length:0.600 inchesStud End Shank Length:0.600 inchesStud End Shank Diameter:0.310 inchesNut End Shank Diameter:0.330 inchesMaterial:Iron alloy 660Material Specification:Ams 5735 assn standard single material responseSurface Treatment:PassivateShouldered and steppedThread Series Designator:Uns stud threadSheff Life:N/a	Shoulder Length:	
Between 2.050 inchess and 2.070 inchessNut End Shank Length:Between 0.278 inches and 0.298 inchessThready Qty Per Inch (tpi):14 stud threadHardness Rating:Between 24.0 rockwell c and 37.0 rockwell cThread Size:0.437 inches stud threadStud End Shank Length:0.600 inchesStud End Shank Length:0.600 inchesStud End Shank Diameter:0.310 inchesNut End Shank Diameter:0.330 inchesMaterial:Iron alloy 660Surface Treatment:PassivateSyled End steppedThread Sizes standard single material responseSurface Treatment:PassivateShouldered and steppedThread Series Designator:Uns stud threadShelf Life:N/a	Between 0.093 inches and 0.095 inches	
Nut End Shank Length:         Between 0.278 inches and 0.298 inches         Thready Qty Per Inch (tpi):         14 stud thread         Hardness Rating:         Between 24.0 rockwell c and 37.0 rockwell c         Thread Size:         0.437 inches stud thread         Stud End Shank Length:         0.600 inches         Stud End Shank Length:         0.600 inches         Stud End Shank Diameter:         0.310 inches         Nut End Shank Diameter:         0.330 inches         Material:         Iron alloy 660         Material Specification:         Ams 5735 assn standard single material response         Surface Treatment:         Passivate         Shuldered and stepped         Thread Series Designator:         Uns stud thread         Sheif Life:         N/a	Overall Length:	
Between 0.278 inches and 0.298 inchesThready Qty Per Inch (tpi):14 stud threadHardness Rating:Between 24.0 rockwell c and 37.0 rockwell cThread Size:0.437 inches stud threadStud End Shank Length:0.600 inchesStud End Shank Length:0.600 inchesStud End Shank Diameter:0.310 inchesMut End Shank Diameter:0.330 inchesMaterial:Iron alloy 660Material Specification:Ams 5735 assn standard single material responseSurface Treatment:PassivateShouldered and steppedThread Series Designator:Uns stud threadMaterialShouldered and steppedShelf Life:N/a	Between 2.050 inches and 2.070 inches	
Thready Qty Per Inch (tpi): 14 stud thread Hardness Rating: Between 24.0 rockwell c and 37.0 rockwell c Thread Size: 0.437 inches stud thread Stud End Shank Length: 0.600 inches Stud End Shank Diameter: 0.310 inches Nut End Shank Diameter: 0.330 inches Material: Iron alloy 660 Material Specification: Ams 5735 assn standard single material response Surface Treatment: Passivate Style Designator: Shouldered and stepped Thread Series Designator: Uns stud thread Shelf Life: N/a	Nut End Shank Length:	
14 stud thread Hardness Rating: Between 24.0 rockwell c and 37.0 rockwell c Thread Size: 0.437 inches stud thread Stud End Shank Length: 0.600 inches Stud End Shank Diameter: 0.300 inches Nut End Shank Diameter: 0.310 inches Nut End Shank Diameter: 0.330 inches Material: Iron alloy 660 Material Specification: Arns 5735 assn standard single material response Surface Treatment: Passivate Style Designator: Shouldered and stepped Thread Series Designator: Uns stud thread Shelf Life: N/a	Between 0.278 inches and 0.298 inches	
Hardness Rating:         Between 24.0 rockwell c and 37.0 rockwell c         Thread Size:         0.437 inches stud thread         Stud End Shank Length:         0.600 inches         Stud End Shank Diameter:         0.310 inches         Nut End Shank Diameter:         0.330 inches         Material:         Iron alloy 660         Material Specification:         Arns 5735 assn standard single material response         Surface Treatment:         Passivate         Shouldered and stepped         Thread Series Designator:         Uns stud thread         Shelf Life:         N/a	Thready Qty Per Inch (tpi):	
Between 24.0 rockwell c and 37.0 rockwell cThread Size:0.437 inches stud threadStud End Shank Length:0.600 inchesStud End Shank Diameter:0.310 inchesNut End Shank Diameter:0.330 inchesMaterial:Iron alloy 660Material Specification:Ams 5735 assn standard single material responseSurface Treatment:PassivateShouldered and steppedThread Series Designator:Uns stud threadShelf Life:N/a	14 stud thread	
Thread Size:0.437 inches stud threadStud End Shank Length:0.600 inchesStud End Shank Diameter:0.310 inchesNut End Shank Diameter:0.330 inchesMaterial:Iron alloy 660Material Specification:Arns 5735 assn standard single material responseSurface Treatment:PassivateStyle Designator:Shouldered and steppedThread Series Designator:Uns stud threadShelf Life:N/a	Hardness Rating:	
0.437 inches stud thread Stud End Shank Length: 0.600 inches Stud End Shank Diameter: 0.310 inches Nut End Shank Diameter: 0.330 inches Material Shank Diameter: 10.330 inches Material: Iron alloy 660 Material Specification: Ams 5735 assn standard single material response Surface Treatment: Passivate Style Designator: Shouldered and stepped Thread Series Designator: Uns stud thread Shelf Life: N/a	Between 24.0 rockwell c and 37.0 rockwell c	
Stud End Shank Length: 0.600 inches Stud End Shank Diameter: 0.310 inches Nut End Shank Diameter: 0.330 inches Material Shank Diameter: 0.330 inches Material: Iron alloy 660 Material Specification: Ams 5735 assn standard single material response Surface Treatment: Passivate Style Designator: Shouldered and stepped Thread Series Designator: Uns stud thread Shelf Life: N/a	Thread Size:	
0.600 inches Stud End Shank Diameter: 0.310 inches Nut End Shank Diameter: 0.330 inches Material: Ionalloy 660 Material Specification: Ams 5735 assn standard single material response Surface Treatment: Passivate Style Designator: Shouldered and stepped Thread Series Designator: Uns stud thread Shelf Life: N/a	0.437 inches stud thread	
Stud End Shank Diameter:0.310 inchesNut End Shank Diameter:0.330 inchesMaterial:0.330 inchesMaterial:Iron alloy 660Material Specification:Ams 5735 assn standard single material responseSurface Treatment:PassivateStyle Designator:Shouldered and steppedThread Series Designator:Uns stud threadShelf Life:N/a	Stud End Shank Length:	
0.310 inches Nut End Shank Diameter: 0.330 inches Material: Iron alloy 660 Material Specification: Ams 5735 assn standard single material response Surface Treatment: Passivate Style Designator: Shouldered and stepped Thread Series Designator: Uns stud thread Shelf Life: N/a	0.600 inches	
Nut End Shank Diameter:0.330 inchesMaterial:Iron alloy 660Material Specification:Ams 5735 assn standard single material responseSurface Treatment:PassivateStyle Designator:Shouldered and steppedThread Series Designator:Uns stud threadShelf Life:N/a	Stud End Shank Diameter:	
0.330 inches Material: Iron alloy 660 Material Specification: Ams 5735 assn standard single material response Surface Treatment: Passivate Style Designator: Shouldered and stepped Thread Series Designator: Uns stud thread Shelf Life: N/a	0.310 inches	
Material:Iron alloy 660Material Specification:Ams 5735 assn standard single material responseSurface Treatment:PassivateStyle Designator:Shouldered and steppedThread Series Designator:Uns stud threadShelf Life:N/a	Nut End Shank Diameter:	
Iron alloy 660 Material Specification: Ams 5735 assn standard single material response Surface Treatment: Passivate Passivate Style Designator: Shouldered and stepped Thread Series Designator: Uns stud thread Shelf Life: N/a	0.330 inches	
Material Specification:Ams 5735 assn standard single material responseSurface Treatment:PassivateStyle Designator:Shouldered and steppedThread Series Designator:Uns stud threadShelf Life:N/a	Material:	
Ams 5735 assn standard single material response Surface Treatment: Passivate Style Designator: Shouldered and stepped Thread Series Designator: Uns stud thread Shelf Life: N/a	Iron alloy 660	
Surface Treatment:   Passivate   Style Designator:   Shouldered and stepped   Thread Series Designator:   Uns stud thread   Shelf Life:   N/a	Material Specification:	
Passivate Style Designator: Shouldered and stepped Thread Series Designator: Uns stud thread Shelf Life: N/a	Ams 5735 assn standard single material response	
Style Designator:         Shouldered and stepped         Thread Series Designator:         Uns stud thread         Shelf Life:         N/a	Surface Treatment:	
Shouldered and stepped Thread Series Designator: Uns stud thread Shelf Life: N/a	Passivate	
Thread Series Designator: Uns stud thread Shelf Life: N/a	Style Designator:	
Uns stud thread Shelf Life: N/a	Shouldered and stepped	
Shelf Life: N/a	Thread Series Designator:	
N/a	Uns stud thread	
	Shelf Life:	
Unit Of Measure:	N/a	
	Unit Of Measure:	

---

Shouldered And Stepped Stud - Page 2 of 2

AeroBase Group

Demilitarization:

No

Fiig:

A051a0