## NSN 5307-00-706-8769

Stepped Stud - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5307-00-706-8769

| Thread Class:                                    |
|--|
| 3a nut thread                                    |
| Thread Pitch Diameters:                          |
| +0.2780 to 0.2795 inches stud thread             |
| Thread Direction:                                |
| Right-hand stud thread                           |
| Thread Length:                                   |
| 0.490 inches and 0.510 inches nut thread         |
| Shank Diameter:                                  |
| Between 0.221 inches and 0.231 inches            |
| Overall Length:                                  |
| Between 1.084 inches and 1.104 inches            |
| End Application:                                 |
| Spec item  |
| Thready Qty Per Inch (tpi):                      |
| 28 nut thread                                    |
| Hardness Rating:                                 |
| Between 26.0 rockwell c and 32.0 rockwell c      |
| Thread Size:                                     |
| 0.312 inches stud thread                         |
| Surface Finish:                                  |
| 63.0 microinches shank                           |
| Material:  |
| Steel comp 8740                                  |
| Material Specification:                          |
| Ams 6322 assn standard single material response  |
| Surface Treatment:                               |
| Cadmium  |
| Surface Treatment Specification:                 |
| Ams 2400 assn standard single treatment response |
| Style Designator:                                |
| Stepped  |
| Thread Series Designator:                        |
| Uns stud thread                                  |
| Shelf Life:                                      |
| N/a  |
| Unit Of Measure:                                 |
|  |
| Demilitarization:                                |
| No   |
| Fiig:  |
| A051a0   |
|  |