NSN 5307-00-764-4227

Locked In Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-00-764-4227

| View Online at https://aerobasegroup.com/nsn/5307-00-764-4227 |
|--|
| Thread Class: |
| 3a nut thread |
| Thread Pitch Diameters: |
| +0.3358/+0.3378 inches stud thread |
| Thread Direction: |
| Right-hand nut thread |
| Thread Length: |
| 0.810 inches nut thread |
| Locking Feature: |
| Ring, lock serrated |
| Overall Length: |
| 1.790 inches |
| Distance From Serrated Portion To Nut End: |
| 0.910 inches |
| Distance From Serrated Portion To Stud End: |
| 0.880 inches |
| Distance From Serrated Portion To End Of Stud Thread: |
| 0.180 inches |
| Serration Quantity: |
| 20 |
| Thready Qty Per Inch (tpi): |
| 24 nut thread |
| Thread Size: |
| 0.375 inches stud thread |
| Material: |
| Steel comp 4130 |
| Material Specification: |
| Mil-s-6758 military specification single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 3 federal specification single treatment response |
| Style Designator: |
| Locked in |
| Thread Series Designator: |
| Unf nut thread |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5307-00-764-4227

Locked In Stud - Page 2 of 2

Fiig: A051a0 Mil-std (military Standard):

Mil-s-6758 spec.

