NSN 5307-00-799-2248

Shouldered And Stepped Stud - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5307-00-799-2248 **Thread Class:** 3a stud thread **Thread Direction:** Right-hand stud thread Thread Length: 0.790 inches stud thread and 0.800 inches stud thread **Shoulder Length:** Between 0.097 inches and 0.107 inches **Overall Length:** Between 2.316 inches and 2.362 inches **Nut End Shank Length:** Between 1.004 inches and 1.010 inches **Distance From Cotter Pin Hole Centerline To Nut End:** 0.144 inches first hole and 0.163 inches first hole **Cotter Pin Hole Diameter:** 0.062 inches first hole and 0.065 inches first hole **Distance Across Flats:** Between 0.865 inches and 0.877 inches Thready Qty Per Inch (tpi): 28 nut thread Hardness Rating: Between 34.0 rockwell c and 38.0 rockwell c **Thread Size:** 0.375 inches stud thread **Nut End Shank Diameter:** Between 0.374 inches and 0.375 inches Material: Steel **Material Specification:** Ams 5643 assn standard single material response **Style Designator:** Shouldered and stepped **Thread Series Designator:** Unf stud thread Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A051a0