NSN 5307-00-811-5680

Plain Stud - Page 1 of 1



0-811-5680

| View Online at https://aerobasegroup.com/nsn/5307-00-81 |
|---------------------------------------------------------|
| Thread Pitch Diameters: |
| +0.2278/+0.2293 inches stud thread |
| Thread Direction: |
| Right-hand stud thread |
| Thread Length: |
| 0.678 inches stud thread and 0.698 inches stud thread |
| Overall Length: |
| Between 1.802 inches and 1.822 inches |
| Distance From Cotter Pin Hole Centerline To Nut End: |
| 0.110 inches first hole |
| Cotter Pin Hole Diameter: |
| 0.065 inches first hole and 0.072 inches first hole |
| Thready Qty Per Inch (tpi): |
| 28 nut thread |
| Hardness Rating: |
| Between 26.0 rockwell c and 32.0 rockwell c |
| Thread Size: |
| 0.250 inches stud thread |
| Surface Finish: |
| 63.0 microinches shank |
| Material: |
| Steel comp 8740 |
| Material Specification: |
| Ams 6322 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Ams 2400 assn standard single treatment response |
| Thread Series Designator: |
| Unf nut thread |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig:

A051a0