NSN 5307-00-843-5965

Stepped Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-00-843-5965

| Thread Class: |
|---|
| 3a nut thread |
| Thread Pitch Diameters: |
| +0.2308/+0.2323 inches stud thread |
| Thread Direction: |
| Right-hand stud thread |
| Thread Length: |
| 0.365 inches stud thread and 0.385 inches stud thread |
| Shank Diameter: |
| Between 0.164 inches and 0.174 inches |
| Overall Length: |
| Between 0.990 inches and 1.010 inches |
| Distance From Cotter Pin Hole Centerline To Nut End: |
| 0.100 inches first hole and 0.120 inches first hole |
| Cotter Pin Hole Diameter: |
| 0.065 inches first hole and 0.072 inches first hole |
| Thready Qty Per Inch (tpi): |
| 32 nut thread |
| Hardness Rating: |
| Between 26.0 rockwell c and 32.0 rockwell c |
| Thread Size: |
| 0.250 inches stud thread |
| Surface Finish: |
| 63.0 microinches shank |
| Material: |
| Steel comp 8740 |
| Material Specification: |
| Ams 6322 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Ams 2400 assn standard single treatment response |
| Style Designator: |
| Stepped |
| Thread Series Designator: |
| Unf nut thread |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5307-00-843-5965 Stepped Stud - Page 2 of 2

Fiig: A051a0

