## NSN 5307-00-902-5216

Stepped Stud - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5307-00-902-5216

| Thread Class:  |
|--|
| 3a nut thread  |
| Thread Pitch Diameters:                              |
| +0.3422/+0.3437 inches stud thread                   |
| Thread Direction:                                    |
| Right-hand stud thread                               |
| Thread Length:                                       |
| 0.750 inches stud thread                             |
| Shank Diameter:                                      |
| Between 0.279 inches and 0.289 inches                |
| Overall Length:                                      |
| 3.188 inches   |
| Distance From Cotter Pin Hole Centerline To Nut End: |
| 0.110 inches first hole                              |
| Cotter Pin Hole Diameter:                            |
| 0.065 inches first hole and 0.072 inches first hole  |
| Thready Qty Per Inch (tpi):                          |
| 24 nut thread  |
| Hardness Rating:                                     |
| Between 26.0 rockwell c and 32.0 rockwell c          |
| Thread Size:   |
| 0.375 inches stud thread                             |
| Material:  |
| Steel comp 8740                                      |
| Material Specification:                              |
| Ams 6322 assn standard single material response      |
| Surface Treatment:                                   |
| Cadmium  |
| Style Designator:                                    |
| Stepped  |
| Thread Series Designator:                            |
| Uns stud thread                                      |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:                                     |
|  |
| Demilitarization:                                    |
| No   |
| Fiig:  |
| A051a0   |
|  |