NSN 5307-00-930-0048

Shouldered Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-00-930-0048
Thread Class:
3a nut thread3a stud thread
Thread Direction:
Right-hand nut threadright-hand stud thread
Thread Length:
0.312 inches nut thread
Shoulder Diameter:
Between 0.325 inches and 0.354 inches
Shoulder Length:
Between 0.064 inches and 0.074 inches
Overall Length:
0.864 inches
Nut End Shank Length:
0.562 inches
Thready Qty Per Inch (tpi):
32 nut thread32 stud thread
Thread Size:
0.190 inches nut thread0.190 inches stud thread
Surface Finish:
32.0 microinches shank
Nut End Shank Diameter:
Between 0.1885 inches and 0.1895 inches
Special Features:
160000 to 180000 psi; socket drive 0.0791 in. Min to 0.0806 in.
Material:
Steel comp 4140 or steel comp 8740 or steel comp 4130
Material Specification:
Mil-s-5626 military specification 1st material response or mil-w-6049 military specification 2nd material response or mil-s-6758 military
specification 3rd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Style Designator:
Shouldered
Thread Series Designator:
Unjf nut threadunjf stud thread
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

NSN 5307-00-930-0048

Shouldered Stud - Page 2 of 2



Fiig:

A051a0

Mil-std (military Standard):

Mil-s-5626 spec.