## NSN 5307-00-942-5580

Recessed And Stepped Stud - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5307-00-942-5580 **Thread Class:** 3a stud thread **Thread Direction:** Right-hand stud thread Thread Length: 1.000 inches stud thread and 1.100 inches stud thread **Overall Length:** Between 7.020 inches and 9.080 inches **Length Of Recessed Portion Of Shank:** Between 0.290 inches and 0.310 inches **Diameter Of Recessed Portion Of Shank:** Between 0.240 inches and 0.252 inches **Distance From Cotter Pin Hole Centerline To Nut End:** 0.120 inches first hole and 0.130 inches first hole **Cotter Pin Hole Diameter:** 0.062 inches first hole and 0.075 inches first hole Thready Qty Per Inch (tpi): 24 stud thread **Thread Size:** 0.312 inches stud thread **Special Features:** Recessed at both ends of shank Material: Steel comp 310 or steel or steel **Material Specification:** Aisi310 assn standard 1st material response and ams5613 assn standard 2nd material response and ms7470 military specification single material response **Surface Treatment: Passivate Style Designator:** Recessed and stepped **Thread Series Designator:** Unf stud thread Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

spec.

A051a0

Mil-std (military Standard):