NSN 5307-00-965-5686

Locked In Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-00-965-5686 **Thread Class:** 3a nut thread **Thread Pitch Diameters:** +0.3926/+0.3946 inches stud thread **Thread Direction:** Right-hand stud thread Thread Length: 0.620 inches nut thread **Locking Feature:** Ring, lock serrated **Overall Length:** 1.630 inches **Distance From Serrated Portion To Nut End:** 0.880 inches **Distance From Serrated Portion To Stud End:** 0.750 inches **Distance From Serrated Portion To End Of Stud Thread:** 0.230 inches **Distance From Cotter Pin Hole Centerline To Nut End:** 0.170 inches first hole **Cotter Pin Hole Diameter:** 0.094 inches first hole and 0.097 inches first hole Thready Qty Per Inch (tpi): 24 nut thread **Thread Size:** 0.438 inches stud thread Material: Steel comp 4130 **Material Specification:** Mil-s-6758, cond f military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Style Designator:** Locked in **Thread Series Designator:** Uns stud thread Shelf Life: N/a

Unit Of Measure:

NSN 5307-00-965-5686

Locked In Stud - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A051a0

Mil-std (military Standard):

Mil-s-6758 spec.