## NSN 5307-00-983-6922

Plain Stud - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5307-00-983-6922

| Thread Class:  |
|--|
| 3a stud thread   |
| Thread Direction:  |
| Right-hand stud thread   |
| Thread Length:   |
| 0.470 inches nut thread and 0.550 inches nut thread                    |
| Overall Length:  |
| 1.120 inches   |
| Distance From Cotter Pin Hole Centerline To Nut End:                   |
| 0.110 inches first hole  |
| Cotter Pin Hole Diameter:  |
| 0.065 inches first hole and 0.072 inches first hole                    |
| Features Provided:   |
| Casehardened   |
| Thready Qty Per Inch (tpi):  |
| 28 nut thread  |
| Hardness Rating:   |
| Between 28.0 rockwell c and 34.0 rockwell c                            |
| Thread Size:   |
| 0.250 inches stud thread   |
| Surface Finish:  |
| 125.0 microinches  |
| Material:  |
| Steel comp 1015 or steel comp 1025                                     |
| Surface Treatment:   |
| Cadmium  |
| Surface Treatment Specification:                                       |
| Qq-p-416, type 1, cl 3 federal specification single treatment response |
| Thread Series Designator:  |
| Unf nut thread   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A051a0   |
|  |
|  |
|  |