NSN 5307-00-993-9220

Shouldered Stud - Page 1 of 1



9220

| View Online at https://aerobasegroup.com/nsn/5307-00-993- |
|-----------------------------------------------------------|
| Thread Pitch Diameters: |
| +0.2860/+0.2884 inches stud thread |
| Thread Direction: |
| Right-hand stud thread |
| Thread Length: |
| 0.695 inches nut thread |
| Shoulder Diameter: |
| Between 0.395 inches and 0.398 inches |
| Shoulder Length: |
| Between 0.080 inches and 0.090 inches |
| Overall Length: |
| Between 1.180 inches and 1.200 inches |
| Distance From Cotter Pin Hole Centerline To Nut End: |
| 0.110 inches first hole |
| Cotter Pin Hole Diameter: |
| 0.065 inches first hole and 0.072 inches first hole |
| Thready Qty Per Inch (tpi): |
| 24 stud thread |
| Thread Size: |
| 0.312 inches stud thread |
| Material Specification: |
| Ams6304 assn standard single material response |
| Surface Treatment: |
| Nickel and cadmium |
| Style Designator: |
| Shouldered |
| Thread Series Designator: |
| Unf stud thread |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| 1051-0 |

A051a0