

View Online at <https://aerobasegroup.com/nsn/5307-01-006-7037>

**General Description:**

Steel, mil-s-5626 or mil-s-6049 or mil-s-6758 stud, fin. Cadmium, qq-p-416, type 1, cl 3 o/a and cetyl alcohol lubricant, min tensile str 160000 psi, double shear str 5380 lb, shouldered stud style, o/a lg 1.176 in. Min and 1.238 in. Max, shoulder diameter 0.357 in. Min and 0.377 in. Max, shoulder lg 0.064 in. Min and 0.074 in. Max, shank dia 0.1885 in. Min and 0.1895 in. Max, nutend shank lg 0.503 in. Min and 0.523 in. Max, nut end thd 0.190-32 unjf 3a rh, nut end thd lg 0.325 in. Nom, stud end thd 190-32 unjf 3a rh, stud end thd lg 0.609 in. Min and 0.641 in. Max, hex. Socket nut end, w across flats 0.0791 in. Min and 0.0806 in. Max, steel, qq-s-764, type 303se collar, fin. Cadmium, qq-p-416, type 1, cl 3 and cetyl alcohol lubricant, collar thd 190-32 unjf 3b rh, collar h 0.437 in. Min and 0.457 in. Max, collar od 0.303 in. Min and 0.307 in. Max, collar id 0.192 in. Min and 0.200 in. Max

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No