NSN 5307-01-048-3845

Continuous Thread Stud - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5307-01-048-3845

Thread Class: 2a Thread Direction: Right-hand Overall Length: 8.000 inches Features Provided: Casehardened Thready Qty Per Inch (tpi): 8 Hardness Rating: Between 25.0 rockwell c and 34.0 rockwell c Thread Ste: 1.125 inches Criticality Code Justification: Zzzw Material: Stel Thread Steis Designator: Un Quality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 items Sheff Life: Na Dird Measure: Image: Audity control iaw navships 0948-045-7010 materials identification and control instruction for level 1 items Na Dird Measure: Image: Na Dird Measure: Image: Audition: Image: Audition: Image: Audition: Image: Audition: Image:	
Thread Direction: Right-hand Overall Length: 8.000 inches Features Provided: Casehardened Thready Oty Per Inch (tpi): 8 Hardness Rating: Between 25.0 rockwell c and 34.0 rockwell c Thread Size: 1.125 inches Criticality Code Justification: Zzzw Material: Steel Departure From Cited Document: Quality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 liters Na Uht Of Measure: - Pointilarization: No Fig: Austial Fig: Austial Fig: Austial Steel Life: Na Dirt of Measure: - Parture From Cited Document = I No Steel Life: Na Dirt of Measure: - Parture: No Fig:	Thread Class:
Right-hand Overall Length: 8.000 inches Features Provided: Casehardened Thready Qty Per Inch (tpi): 8 Hardness Rating: Between 25.0 rockwell c and 34.0 rockwell c Thread Size: 1.125 inches Criticality Code Justification: Zzzw Material: Steel During Size: Outige Steing Designator: Un Steel Duality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 items Sheff Life: Na Chit Of Measure: Image: No Fig: A051a0	2a
Overall Length: 8.000 inches Features Provided: Casehardened Thready Qty Per Inch (tpi): 8 Hardness Rating: Between 25.0 rockwell c and 34.0 rockwell c Thread Size: 1.125 inches Criticality Code Justification: Zzzw Material: Steel Thread Size: Quality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 items Sheff Life: Na Duality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 items Sheff Life: Na Duality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 items Sheff Life: Na Duality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 items Sheff Life: Na Duality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 items Sheff Life: Na Gatian Gatian Ditem Control iaw navships 0948-045-7010 mat	Thread Direction:
8.000 inches Features Provided: Casehardened Thready Qty Per Inch (tpi): 8 Hardness Rating: Between 25.0 rockwell c and 34.0 rockwell c Thread Size: 1.125 inches Criticality Code Justification: Zzzw Material: Steel Thread Series Designator: Un Departure From Cited Document: Nality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 items Shelf Life: N/a Ensure: Na Fig: A001 Fig: A051a0	Right-hand
Features Provided: Casehardened Thready Qty Per Inch (tpi): 8 Hardness Rating: Between 25.0 rockwell c and 34.0 rockwell c Thread Size: 1.125 inches Criticality Code Justification: Zzzw Material: Steel Thread Series Designator: Un Departure From Cited Document: Nality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 items Shelf Life: N/a Duality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 items Shelf Life: N/a Ensite Series: Stel The Advection: Na Stel Series: Na Stel Series: Na Stel Series: Stel Series: <	Overall Length:
CasehardenedThready Qty Per Inch (tpi):8Hardenss Rating:Between 25.0 rockwell c and 34.0 rockwell cThread Size:1.125 inchesChticality Code Justification:ZzzwMaterial:SteelThread Series Designator:UnDeparture From Cited Document:Na'Na'Inf Measure:Inf Measure:Parellitarization:StelDiri of Measure:Na'Diri of Measure:Fig:NaFig:AtofaloHinstop Standard):StafaloFig:AtofaloHinstop Standard):Stafalo<	8.000 inches
Thready Qty Per Inch (tpi): 8 Hardness Rating: Between 25.0 rockwell c and 34.0 rockwell c Thread Size: 1.125 inches Criticality Code Justification: Zzzw Material: Steel Thread Series Designator: Un Paparture From Cited Document: Nal Nal Into Measure: Into Measure: Into Measure: Na Stell Differiation: Nal Differiation: Nal Stell Life: Nal Stell Life: Nal Differiation: Stell Life: Nal Stell Life: Nal <	Features Provided:
8 Hardness Rating: Between 25.0 rockwell c and 34.0 rockwell c Thread Size: 1.125 inches Criticality Code Justification: Criticality Code Justification: Zzzw Material: Zzw Material: Steel Thread Series Designator: Un Poparture From Cited Document: Quality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 items Sheff Life: N/a Chi Of Measure: Fomilitarization: No Fig: Au51a0 Mi-st (military Standard):	Casehardened
Hardness Rating:Between 25.0 rockwell c and 34.0 rockwell cThread Size:1.125 inchesCriticality Code Justification:ZzzwMaterial:SteelThread Series Designator:UnDeparture From Cited Document:Nality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 itemsNality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 itemsShelf Life:N/aInto of Measure:Femilitarization:NoFig:Atosia0Mi-standard):	Thready Qty Per Inch (tpi):
Between 25.0 rockwell c and 34.0 rockwell cThread Size:1.125 inchesCriticality Code Justification:ZzzwZztwMaterial:SteelThread Series Designator:UnDeparture From Cited Document:Quality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 itemsShelf Life:N/aUnit Of Measure:-Demilitarization:NoFig:A051a0Milest (military Standard):	8
Hread Size:1.125 inchesCriticality Code Justification:ZzzwZzawMaterial:SteelThread Series Designator:UnDeparture From Cited Document:Quality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 itemsShelf Life:N/aUnit Of Measure:-Pomilitarization:NoFig:A051a0Miltary Standard):	Hardness Rating:
1.125 inches Criticality Code Justification: Zzzw Zzzw Material: Steel Thread Series Designator: Un Cup	Between 25.0 rockwell c and 34.0 rockwell c
Criticality Code Justification:ZzzwMaterial:SteelThread Series Designator:UnDeparture From Cited Document:Quality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 itemsShelf Life:N/aUni Of Measure:Imilitarization:NoFig:A051a0Mil-stu (military Standard):	Thread Size:
ZzzwMaterial:SteelThread Series Designator:UnDeparture From Cited Document:Quality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 itemsShelf Life:N/aUnit Of Measure:Pomilitarization:NoFig:A051a0Mil-std (military Standard):	1.125 inches
Material:SteelThread Series Designator:UnDeparture From Cited Document:Quality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 itemsShelf Life:N/aUni Of Measure:Demilitarization:NoFig:A051a0Mil-sto (military Standard):	Criticality Code Justification:
Steel Thread Series Designator: Un Departure From Cited Document: Quality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 items Shelf Life: N/a N/a Unit Of Measure: Demilitarization: No Fig: A051a0 Mil-std (military Standard):	Zzzw
Thread Series Designator:UnDeparture From Cited Document:Quality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 itemsShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:A051a0Mil-stat (military Standard):	Material:
Un Departure From Cited Document: Quality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 items Shelf Life: N/a Via Unit Of Measure: Demilitarization: No Fig: A051a0 Mil-std (military Standard):	Steel
Departure From Cited Document:Quality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 itemsShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:A051a0Mil-std (military Standard):	Thread Series Designator:
Quality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 items Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A051a0 Mil-std (military Standard):	Un
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A051a0 Mil-std (military Standard):	Departure From Cited Document:
N/a Unit Of Measure: Demilitarization: No Fiig: A051a0 Mil-std (military Standard):	Quality control iaw navships 0948-045-7010 materials identification and control instruction for level 1 items
Unit Of Measure: Demilitarization: No Fiig: A051a0 Mil-std (military Standard):	Shelf Life:
Demilitarization: No Fiig: A051a0 Mil-std (military Standard):	N/a
Demilitarization: No Fiig: A051a0 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A051a0 Mil-std (military Standard):	
Fiig: A051a0 Mil-std (military Standard):	Demilitarization:
A051a0 Mil-std (military Standard):	No
Mil-std (military Standard):	Filg:
	A051a0
Mil-dtl-1222 spec.	Mil-std (military Standard):
	Mil-dtl-1222 spec.