NSN 5307-01-097-8996

Locked In Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-01-097-8996

Thread Class: 3a nut thread **Thread Pitch Diameters:** +0.2869/+0.2884 inches stud thread **Thread Direction:** Right-hand stud thread Thread Length: 0.405 inches stud thread and 0.435 inches stud thread **Locking Feature:** Ring, lock serrated **Overall Length:** Between 1.468 inches and 1.528 inches **Distance From Serrated Portion To Nut End:** Between 0.923 inches and 0.953 inches **Distance From Serrated Portion To Stud End:** Between 0.545 inches and 0.575 inches **Distance From Serrated Portion To End Of Stud Thread:** Between 0.110 inches and 0.170 inches **Serration Quantity:** 17 Thready Qty Per Inch (tpi): 28 nut thread **Hardness Rating:** 26.0 rockwell c **Thread Size:** 0.312 inches stud thread **Serration Included Angle:** 86.0 degrees **Product Name:** Navy special project Material: Steel comp 4130 **Material Specification:** Mil-s-6758 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Style Designator:** Locked in

Thread Series Designator:

Unf stud thread

NSN 5307-01-097-8996

Locked In Stud - Page 2 of 2



N/a	
Unit Of	Measure:

Shelf Life:

Demilitarization:

No

Fiig:

A051a0

Mil-std (military Standard):

Mil-s-6758 spec.