NSN 5307-01-100-3766

Shouldered Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-01-100-3766

Thread Class:
3a stud thread
Thread Direction:
Right-hand stud thread
Thread Length:
1.054 inches nut thread and 1.074 inches nut thread
Shoulder Diameter:
Between 0.840 inches and 0.860 inches
Shoulder Length:
Between 0.100 inches and 0.110 inches
Overall Length:
Between 5.347 inches and 5.367 inches
Nut End Shank Length:
Between 1.097 inches and 1.117 inches
Thready Qty Per Inch (tpi):
20 stud thread
Hardness Rating:
Between 46.0 rockwell c and 49.0 rockwell c
Thread Size:
0.500 inches stud thread
Stud End Shank Length:
Between 2.150 inches and 2.170 inches
Stud End Shank Diameter:
0.499 inches
Nut End Shank Diameter:
0.499 inches
Special Features:
37, 800 lbs tensile strength
Material:
Steel comp 4330
Material Specification:
Ams 6411 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Mil-c-8837, type 2, class 2 military specification 1st treatment response or 1500, type 2, class 2 military standard 2nd treatment response
Style Designator:
Shouldered
Thread Series Designator:
Unjf stud thread

N/a

Shelf Life:

NSN 5307-01-100-3766

Shouldered Stud - Page 2 of 2



Unit Of Mea	sure:
-------------	-------

--

Demilitarization:

No

Fiig:

A051a0

Mil-std (military Standard):

Mil-c-8837 spec.