NSN 5307-01-130-0656

Locked In Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-01-130-0656

····· •····· •····· •···· •··· •·· •··· •··· •·· •·· •·· •·· •·· •·· •·· •·· •·· •·· •·· •·· •·· •·· •·· •·· •·
Thread Class:
3a nut thread
Thread Pitch Diameters:
+0.2869/+0.2884 inches stud thread
Thread Direction:
Right-hand stud thread
Thread Length:
0.454 inches nut thread and 0.484 inches nut thread
Locking Feature:
Ring, lock serrated
Overall Length:
Between 0.960 inches and 1.030 inches
Distance From Serrated Portion To Nut End:
Between 0.547 inches and 0.577 inches
Distance From Serrated Portion To Stud End:
Between 0.413 inches and 0.453 inches
Distance From Serrated Portion To End Of Stud Thread:
Between 0.113 inches and 0.143 inches
Serration Quantity:
13
Thready Qty Per Inch (tpi):
32 nut thread
Hardness Rating:
277.0 rockwell b
Thread Size:
0.312 inches stud thread
Surface Finish:
63.0 microinches shank
Serration Included Angle:
Between 101.0 degrees and 104.0 degrees
Material:
Iron alloy 660
Material Specification:
Ams 5734 assn standard single material response
Style Designator:
Locked in
Thread Series Designator:
Uns stud thread
Shelf Life:
N/a
Unit Of Measure:

NSN 5307-01-130-0656

Locked In Stud - Page 2 of 2

Demilitarization:

No

Fiig:

A051a0

