## NSN 5307-01-134-5897

Locked In Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-01-134-5897

**Thread Class:** 

3a nut thread

**Thread Pitch Diameters:** 

+0.3358/+0.3378 inches stud thread

**Thread Direction:** 

Right-hand stud thread

**Thread Length:** 

0.545 inches nut thread and 0.575 inches nut thread

**Locking Feature:** 

Ring, lock serrated

**Overall Length:** 

Between 2.035 inches and 2.095 inches

**Distance From Serrated Portion To Nut End:** 

Between 1.360 inches and 1.390 inches

**Distance From Serrated Portion To Stud End:** 

Between 0.675 inches and 0.705 inches

**Distance From Serrated Portion To End Of Stud Thread:** 

Between 0.150 inches and 0.210 inches

**Serration Quantity:** 

20

Thready Qty Per Inch (tpi):

24 nut thread

**Hardness Rating:** 

26.0 rockwell c

**Thread Size:** 

0.375 inches stud thread

Surface Finish:

32.0 microinches stud thd

Serration Included Angle:

102.0 degrees

Material:

Steel comp 4130

**Material Specification:** 

Mil-s-6758 military specification single material response

**Surface Treatment:** 

Cadmium and chromate

**Surface Treatment Specification:** 

Qq-p-416 ty2 cl3 federal specification single treatment response

**Style Designator:** 

Locked in

**Thread Series Designator:** 

Unf nut thread

## NSN 5307-01-134-5897

Locked In Stud - Page 2 of 2



| N/a               |
|-------------------|
| Unit Of Measure:  |
|                   |
| Demilitarization: |
| No                |
| Fiig:             |
| A051a0            |

Mil-std (military Standard):

Mil-s-6758 spec.

Shelf Life: