NSN 5307-01-134-8798

Locked In Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-01-134-8798

Thread Class:

3a nut thread

Thread Pitch Diameters:

+0.2778/+0.2795 inches stud thread

Thread Direction:

Right-hand stud thread

Thread Length:

0.375 inches stud thread and 0.405 inches stud thread

Locking Feature:

Ring, lock serrated

Overall Length:

Between 2.000 inches and 2.120 inches

Distance From Serrated Portion To Nut End:

Between 1.455 inches and 1.545 inches

Distance From Serrated Portion To Stud End:

Between 0.545 inches and 0.575 inches

Distance From Serrated Portion To End Of Stud Thread:

Between 0.140 inches and 0.200 inches

Serration Quantity:

17

Thready Qty Per Inch (tpi):

28 nut thread

Hardness Rating:

26.0 rockwell c

Thread Size:

0.312 inches stud thread

Serration Included Angle:

Between 85.0 degrees and 88.0 degrees

Material:

Steel comp 4130

Material Specification:

Mil-s-6758 military specification single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, ty2, cl3 federal specification single treatment response

Style Designator:

Locked in

Thread Series Designator:

Uns stud thread

Shelf Life:

N/a

NSN 5307-01-134-8798

Locked In Stud - Page 2 of 2



		• -						
ш	ın	ıt (r 1t	ΝЛ	മാ	CI.	ire:	•

--

Demilitarization:

No

Fiig:

A051a0

Mil-std (military Standard):

Mil-s-6758 spec.