NSN 5307-01-149-1403

Shouldered Stud - Page 1 of 2

Shelf Life:

N/a



View Online at https://aerobasegroup.com/nsn/5307-01-149-1403

Thread Class: 3a stud thread **Thread Direction:** Right-hand stud thread Thread Length: 1.196 inches nut thread and 1.216 inches nut thread Shoulder Diameter: Between 0.940 inches and 0.960 inches **Shoulder Length:** Between 0.100 inches and 0.110 inches **Overall Length:** Between 6.383 inches and 6.403 inches **Nut End Shank Length:** Between 1.437 inches and 1.457 inches Thready Qty Per Inch (tpi): 18 stud thread **Hardness Rating:** Between 46.0 rockwell c and 49.0 rockwell c **Thread Size:** 0.562 inches stud thread Stud End Shank Length: Between 2.605 inches and 2.625 inches **Stud End Shank Diameter:** 0.561 inches **Nut End Shank Diameter:** 0.561 inches **Special Features:** 47, 900 lbs tensile strength Material: Steel comp 4330 **Material Specification:** Ams 6411 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Mil-c-8837, type 2, class 2 military specification 1st treatment response or 1500, type 2, class 2 military standard 2nd treatment response **Style Designator:** Shouldered **Thread Series Designator:** Unjf stud thread

NSN 5307-01-149-1403

Shouldered Stud - Page 2 of 2



| | | eas | |
|--|--|-----|--|

--

Demilitarization:

No

Fiig:

A051a0

Mil-std (military Standard):

Mil-c-8837 spec.