NSN 5307-01-150-5991

Shouldered Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-01-150-5991

Thread Direction: Right-hand stud thread **Thread Length:** 14.3 millimeters stud thread and 17.0 millimeters stud thread Shoulder Length: Between 7.07 millimeters and 7.53 millimeters Second Shoulder Diameter: Between 9.78 millimeters and 10.00 millimeters Second Shoulder Length: Between 5.4 millimeters and 6.4 millimeters **Overall Length:** Between 79.77 millimeters and 82.53 millimeters Nut End Shank Length: 2.0 millimeters **Distance Across Flats:** Between 14.7 millimeters and 15.0 millimeters **Thread Size:** 10.0 millimeters nut thread **Thread Pitch In Millimeters:** 1.50 nut thread Stud End Shank Length: 26.6 millimeters Stud End Shank Diameter: Between 8.9 millimeters and 9.4 millimeters Nut End Shank Diameter: Between 9.78 millimeters and 10.00 millimeters **Thread Tolerance Class:** 6g external stud thread Material: Steel **Material Specification:** Gm 500-m 9.8 fscm 11862 mfr ref single material response Surface Treatment: Phosphate Surface Treatment Specification: Gm 4435-m code a fscm 11862 mfr ref single treatment response **Style Designator:** Shouldered **Thread Series Designator:** M nut thread Shelf Life: N/a

NSN 5307-01-150-5991

Shouldered Stud - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A051a0

