## NSN 5307-01-158-6312

Shouldered And Stepped Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-01-158-6312

**Thread Direction:** Right-hand stud thread Thread Length: 15.0 millimeters nut thread **Shoulder Length:** Between 8.92 millimeters and 9.68 millimeters **Overall Length:** Between 87.22 millimeters and 89.68 millimeters **Nut End Shank Length:** 31.5 millimeters **Distance Across Flats:** Between 14.7 millimeters and 15.0 millimeters **Hardness Rating:** Between 33.0 rockwell c and 39.0 rockwell c **Thread Size:** 8.0 millimeters nut thread **Thread Pitch In Millimeters:** 1.50 stud thread Stud End Shank Length: 2.5 millimeters **Stud End Shank Diameter:** 8.0 millimeters **Nut End Shank Diameter:** 10.0 millimeters **Thread Tolerance Class:** 6g external stud thread **Special Features:** Extended washer on shoulder 21.5mm maximum diameter and 1.5mm min. Thickness Material: Steel **Material Specification:** G-500-m 10.9, fscm 11862 mfr ref single material response **Surface Treatment:** Phosphate **Surface Treatment Specification:** G-4435-m code a fsc-11862 mfr ref single treatment response **Style Designator:** Shouldered and stepped **Thread Series Designator:** M nut thread Shelf Life:

N/a

## NSN 5307-01-158-6312

Shouldered And Stepped Stud - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A051a0