

View Online at <https://aerobasegroup.com/nsn/5307-01-169-2864>

**Thread Class:**

3a nut thread

**Thread Pitch Diameters:**

+0.3926/+0.3946 inches stud thread

**Thread Direction:**

Right-hand stud thread

**Thread Length:**

0.605 inches nut thread and 0.635 inches nut thread

**Locking Feature:**

Ring, lock serrated

**Overall Length:**

Between 1.345 inches and 1.405 inches

**Distance From Serrated Portion To Nut End:**

Between 0.610 inches and 0.640 inches

**Distance From Serrated Portion To Stud End:**

Between 0.735 inches and 0.765 inches

**Distance From Serrated Portion To End Of Stud Thread:**

Between 0.200 inches and 0.260 inches

**Distance From Cotter Pin Hole Centerline To Nut End:**

0.155 inches first hole and 0.185 inches first hole

**Cotter Pin Hole Diameter:**

0.106 inches first hole

**Serration Quantity:**

24

**Thready Qty Per Inch (tpi):**

24 nut thread

**Hardness Rating:**

26.0 rockwell c

**Thread Size:**

0.438 inches stud thread

**Surface Finish:**

32.0 microinches nut thd

**Serration Included Angle:**

Between 101.0 degrees and 104.0 degrees

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 military specification single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Style Designator:**

Locked in

**Thread Series Designator:**

Uns stud thread

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A051a0

**Mil-std (military Standard):**

Mil-s-6758 spec.