

View Online at <https://aerobasegroup.com/nsn/5307-01-189-3861>

**Thread Class:**

3a nut thread

**Thread Pitch Diameters:**

+0.1639/+0.1654 inches stud thread

**Thread Direction:**

Right-hand stud thread

**Thread Length:**

0.395 inches nut thread and 0.425 inches nut thread

**Locking Feature:**

Ring, lock serrated

**Overall Length:**

1.380 inches

**Distance From Serrated Portion To Nut End:**

Between 0.985 inches and 1.015 inches

**Distance From Serrated Portion To Stud End:**

Between 0.365 inches and 0.395 inches

**Distance From Serrated Portion To End Of Stud Thread:**

Between 0.065 inches and 0.095 inches

**Serration Quantity:**

16

**Thready Qty Per Inch (tpi):**

32 nut thread

**Hardness Rating:**

26.0 rockwell c

**Thread Size:**

0.190 inches stud thread

**Serration Included Angle:**

Between 89.0 degrees and 92.0 degrees

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 military specification single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 class 3 federal specification single treatment response

**Style Designator:**

Locked in

**Thread Series Designator:**

Uns stud thread

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A051a0

**Mil-std (military Standard):**

Mil-s-6758 spec.