NSN 5307-01-197-6670

Shouldered And Stepped Stud - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5307-01-197-6670 **Thread Class:** 3a stud thread **Thread Direction:** Right-hand stud thread Thread Length: 0.448 inches stud thread and 0.531 inches stud thread **Shoulder Length:** Between 0.188 inches and 0.190 inches **Overall Length:** 1.443 inches **Nut End Shank Length:** Between 0.057 inches and 0.067 inches **Distance Across Flats:** Between 0.367 inches and 0.376 inches Thready Qty Per Inch (tpi): 32 nut thread **Thread Size:** 0.312 inches stud thread Stud End Shank Length: Between 0.335 inches and 0.343 inches Stud End Shank Diameter: Between 0.311 inches and 0.312 inches **Nut End Shank Diameter:** Between 0.189 inches and 0.190 inches **Special Features:** Furnished with one o-ring; countersunk on shoulder 0.0878in.Min, 0.0899in. Maximum Ig Material: Titanium alloy uns r56400 **Material Specification:** Ams4967, comp 6al-4v assn standard single material response **Style Designator:** Shouldered and stepped **Thread Series Designator:** Unif stud thread Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A051a0