NSN 5307-01-200-1493

Shouldered And Stepped Stud - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5307-01-200-1493 **Thread Class:** 3a stud thread **Thread Direction:** Right-hand stud thread Thread Length: 0.398 inches stud thread and 0.469 inches stud thread **Shoulder Length:** Between 0.171 inches and 0.173 inches **Overall Length:** 1.568 inches **Nut End Shank Length:** Between 0.057 inches and 0.067 inches **Distance Across Flats:** Between 0.367 inches and 0.376 inches Thready Qty Per Inch (tpi): 32 nut thread **Thread Size:** 0.250 inches stud thread Stud End Shank Length: Between 0.547 inches and 0.559 inches Stud End Shank Diameter: Between 0.249 inches and 0.250 inches **Nut End Shank Diameter:** Between 0.189 inches and 0.190 inches **Special Features:** Furnished with one o-ring; countersunk on shoulder 0.0713in.Min, 0.0733in. Maximum Ig Material: Titanium alloy uns r56400 **Material Specification:** Ams4967, comp 6al-4v assn standard single material response **Style Designator:** Shouldered and stepped **Thread Series Designator:** Unif stud thread Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

· ...g.

A051a0