NSN 5307-01-212-0214

Recessed Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-01-212-0214

an ut thread Thread Directics 40:3010 0.2825 inches stud thread Thread Directics: Right-hand stud thread Thread Directics: Right-hand stud thread Overall Length: 0:432 inches and 1:455 inches Between 1:535 inches nut thread Overall Length: Between 1:535 inches nut 1:555 inches Length Of Recessed Portion Of Shank: O 200 inches O 200 inches O 201 Length: Dateer Of Recessed Portion Of Shank: D 200 inches O 201 Length Between 0.221 inches and 0.231 inches D 202 Unches O 202 Unches D 203 Unches Between 0.221 inches and 0.231 inches Between 0.221 inches and 0.231 inches D 201 Inches D 202 Inches D 202 Inches D 203 Unches D 204 Unches D 205 Unches	View Online at https://aerobasegroup.com/nsn/5307-01-212-0214
Thread Pick Diameters: 42.810 to 0.2825 inches stud thread Thread Direction: Righ-hand stud thread Thread Longth: 0.422 inches and 0.452 inches nut thread Dareat Longth: 0.422 inches and 0.452 inches nut thread Dareat Control of Shank: Longth Of Recessed Portion Of Shank: 0.203 inches Dareat Of Recessed Portion Of Shank: 0.203 inches Batween 0.403 inches and 0.231 inches Batween 0.403 inches and 0.231 inches Batween 0.403 inches inches and 5.0 incokwell o Dareat Stating: 0.312 inches stud thread Special Features: 0.312 inches stud studience Dareat Stating: Dareat Stating: Dareat Stating: Bater Stating: Dareat Stating: Dareat Stating: Bater Stating: Dareat Stating: <th>Thread Class:</th>	Thread Class:
Apple 10.2285 inches sud thread Thread Direction: Right-hand stud thread Add thread thread Add thread stud thread Overall Length: Overall Length: Between 1.555 inches and 1.555 inches Langth Of Recessed Portion Of Shank: 2080 inches Diameter Of Recessed Portion Of Shank: 2080 inches Diameter Of Recessed Portion Of Shank: 2080 inches Diameter Of Recessed Portion Of Shank: 2080 inches Datest of Recessed Portion Of Shank: 2080 inches Between 0.221 inches and 0.231 inches Thread Quty Per Inch (tpl): 24 nut thread Between 40.0 rockwell c and 45.0 rockwell c Thread Stee: 0.312 inches stud thread Surface Finish: 63.0 microinches undercuts Special Features: Unthread escetion dia. 0.3125 inch Material Steel comp 8740 or steel comp 4140 or steel comp 4340 Material Specification: Interest Poster Cadmium and chromate Surface Treatment: Cadmium and chromate <td>3a nut thread</td>	3a nut thread
Thread Direction: Right-hand stud thread Charle Length: 0.432 inches and 0.452 inches nut thread Ovanil Length: Between 1.535 inches and 1.555 inches Length Of Recessed Portion Of Shank: 0.280 inches Diameter Of Recessed Portion Of Shank: Between 0.221 inches and 0.231 inches Thread Qity Per Inch (tpi): 24 nut thread Hardness Rating: Between 40.0 rockwell c and 45.0 rockwell c Thread Storie 0.312 inches stud thread Striede Flatteres: 0.312 inches stud thread Striede Flatteres: 0.312 inches stud thread Striede Flatteres: 0.312 inches stud thread is the storie comp 4340 Material Striede Flatteres: 0.312 inches stud thread is the storie comp 4340 Material Striede Textment: Cadmium and chromate Striede Textment: Querter Textment Specification single treatment response Stried Textment Specification single treatment response Stried Textment Specification single treatment response Stried Textment Specification single tre	Thread Pitch Diameters:
Right-hand stud thread Thread Length: 0.432 Inches and 0.452 Inches nut thread Overall Length: Between 1.535 Inches and 1.555 Inches Length Of Recessed Portion Of Shank: 0.200 Inches Diamet Of Recessed Portion Of Shank: 0.200 Inches Diamet Of Recessed Portion Of Shank: 0.201 Inches and 0.231 Inches Thready Of Per Inch (tpi): 24 nut thread Hardness Rating: 0.312 Inches stud thread 0.312 Inches stud thread Surface Finish: 0.312 Inches stud thread Surface Finish: 0.312 Inches stud thread Surface Finish: 0.301 Inchiches Undercuts Special Features: Unthreadds Station dia. 0.3125 Inch Material: Station dia thread Its material response or arms 6382 asen standard 2nd material response or arms 6415 asen standard 3rd material response or arms 6382 asen standard 2nd material response or arms 6415 asen standard 3rd material response Strafec Treatment: Cadmium and chromate Surface Treatment Specification: Cadmium and chromate Streation: Strafe Streat Spesifica	+0.2810 to 0.2825 inches stud thread
Tread Length: 0.432 inches and 0.432 inches nut thread Overall Length Between 1.535 inches and 1.555 inches Length Of Recessed Portion Of Shank: 0.230 inches Diameter Of Recessed Portion Of Shank: 0.230 inches and 0.231 inches Thread Quy Per Inch (pt): 24 nut thread Between 0.221 inches and 0.231 inches Thread Stein: 0.312 inches stud thread Between 40.0 rockwell c and 45.0 rockwell c Thread Stein: 0.312 inches stud thread Souriaco Finish: 23.0 microinches undercuts Special Features: 0.312 inches stud thread Steic comp 8740 or steel comp 4340 Material Special Features: Surface Treatment: Recensed Surface Treatment: Cardianum and chromate Surface Treatment: Surface Treatment: Cardianum and c	Thread Direction:
0.432 inches and 0.452 inches nut thread Overall Longth: Between 1.535 inches and 1.555 inches Longth Of Recessed Portion Of Shank: 2.80 inches Diameter Of Recessed Portion Of Shank: Between 0.221 inches and 0.231 inches Thread Vp Per Inch (tpi): 24 nut thread Hardness Rating: Between 40.0 rockwell c and 45.0 rockwell c Thread Size: 0.312 inches stud thread Surface Finish: 0.312 inches stud thread Surface Teatment: 0.312 inches stud thread section dia. 0.3125 inch Material Specification: 0.312 inches stud at 1.51 inch Material Specification stud at 1.51 inch Material Specification stud at 1.51 inch	Right-hand stud thread
Overall Length: Between 1.535 inches and 1.555 inches Length Of Recessed Portion Of Shank: 0.200 inches Dameter Of Recessed Portion Of Shank: Between 0.221 inches and 0.231 inches Thready Cly Per Inch (tpi): 24 nut thread Hardness Rating: Between 0.00 rockwell c and 45.0 rockwell c Thread Size: 0.312 inches stud thread Solar inches stud thread Solar inches undercuts Special Features: Unthreaded section dia. 0.3125 inch Material Stel comp 8740 or steel comp 4140 or steel comp 4340 Material Specification: Cadmium and chromate Surface Treatment: Cadmium and chromate Surface Treatment Specifications ingle treatment response Cadmium and chromate Surface Treatment Specification ingle treatment response Style Designator: Naterial Specification: Style Designator: Naterial Specification Style Designator: Style Designator: Naterial Specification single treatment response <	Thread Length:
Between 1.535 inches and 1.555 inches Length Of Recessed Portion Of Shank: 0.280 inches Dameter Of Recessed Portion Of Shank: Between 0.221 inches and 0.231 inches Thread Q1P Per Inb (tp): 24 nut thread Hardness Rating: Between 4.0.0 rockwell c and 45.0 rockwell c Thread Size: 0.312 inches stud thread Solze Finish: 63.0 microinches undercuts Special Features: Unthreaded section dia. 0.3125 inch Material: Stel comp 8740 or steel comp 4140 or steel comp 4340 Material Specification: Cadmium and chromate Surface Treatment Specifications Cadmium and chromate Surface Treatment Specification single treatment response Style Designator: Long Suffication: Que-p-16, tyc, d. 3 federal specification single treatment response Style Designator: Long Suffication: Long Suffication: Long Suffication: Long Ling Ling Ling Ling Ling Ling Ling Li	0.432 inches and 0.452 inches nut thread
Length Of Recessed Portion Of Shank: 0.280 inches Diameter Of Recessed Portion Of Shank: Between 0.221 inches and 0.231 inches Thready Oty Per Inch (tp): 24 nut thread Hardness Rating: Between 40.0 rockwell c and 45.0 rockwell c Thread Size: 0.312 inches stud thread Surface Finish: 63.0 microinches undercuts Special Features: Unthreaded bection dia. 0.3125 inch Material Stel comp 8740 or steel comp 4140 or steel comp 4340 Material Specification: Rufface Treatment: Cadmium and chromate Surface Treatment: Cadmium and chromate Striface	Overall Length:
0.200 inches Diameter Of Recessed Portion Of Shank: Between 0.221 inches and 0.231 inches Between 0.221 inches and 0.231 inches Thready Chy Per Inch (tpi): 24 nut thread Hardiness Rating: Between 40.0 rockwell c and 45.0 rockwell c Thread Size: 0.312 inches stud thread Surface Finish: 63.0 microinches undercuts Special Features: Unthreadd section dia. 0.3125 inch Material Stel comp 8740 or steel comp 4140 or steel comp 4340 Material Specification: Ans 6322 assn standard 1st material response or ams 6382 assn standard 2nd material response or ams 6415 assn standard 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment: Que ye have, ye di a federal specification single treatment response Surface Treatment Specification single treatment response Style Designator: Recessed Thread Style Specification: Recessed Thread Style Specification single treatment response Style Designator: Nie Style Markel Style Designator: Nie style Ma	Between 1.535 inches and 1.555 inches
Dimeter Of Recessed Portion Of Shank: Between 0.221 inches and 0.231 inches Thready Qiy Per Inch (up): 24 nut thread Hardness Rating: Between 0.00 rockwell o and 45.0 rockwell o Thread Size: 0.312 inches stud thread Surface Finish: 63.0 microinches undercuts Special Features: Unthreaded section dia. 0.3125 inch Material: Steel comp 8740 or steel comp 4140 or steel comp 4340 Material: Response Surface Treatment: Cadmium and chromate Surface Treatment:	Length Of Recessed Portion Of Shank:
Between 0.221 inches and 0.231 inches Tready Cty Per Inch (tpi): 24 nut thread Hardness Rating: Between 40.0 rockwell c and 45.0 rockwell c Thread Size: 0.312 inches stud thread Surface Finish: 63.0 microinches undercuts Special Features: Unthreadd section dia. 0.3125 inch Material Stel comp 8740 or steel comp 4140 or steel comp 4340 Material Specification: Rans 6322 assn standard 1st material response or ams 6382 assn standard 2nd material response or ams 6415 assn standard 3rd material response Surface Treatment: Cadmium and chromate Style Designator: Recessed Style Designator: Recessed Recessed Style Designator: Uns stud thread Style Designator: Nerdis Style Designator: Nard Style Designator:	0.280 inches
Thready Qty Per Inch (tpi): 24 nut thread 24 nut thread Hardness Rating: Between 40.0 rockwell c and 45.0 rockwell c Thread Size: 0.312 inches stud thread Surface Finish: 63.0 microinches undercuts Special Features: Unthreaded section dia. 0.3125 inch Material: Stel comp 8740 or steel comp 4140 or steel comp 4340 Material Specification: Ams 6322 assn standard 1st material response or ams 6382 assn standard 2nd material response or ams 6415 assn standard 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qup-416, ty2, cl 3 federal specification single treatment response Style Designator: Recessed Chread Seles Designator: Uns stud thread Shef Life: Na	Diameter Of Recessed Portion Of Shank:
Part untread Hardness Rating: Between 40.0 rockwell c and 45.0 rockwell c Thread Size: 0.312 inches stud thread Surface Finish: 63.0 microinches undercuts Special Features: Unthreaded section dia. 0.3125 inch Material: Starf Size: Starf Size: Material: Starf Size: Starf Size: <	Between 0.221 inches and 0.231 inches
Hardness Rating: Between 40.0 rockwell c and 45.0 rockwell c Thread Size: 0.312 inches stud thread Surface Finish: 63.0 microinches undercuts Special Features: Unthreaded section dia. 0.3125 inch Material: Stel comp 8740 or steel comp 4140 or steel comp 4340 Material Specification: Amstel Size assen standard 1st material response or ams 6382 assen standard 2nd material response or ams 6415 assen standard 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qu-p-416, ty2, cl 3 federal specification single treatment response Streac Secient Recessed Thread Series Designator: Recessed Streac Secient Se	Thready Qty Per Inch (tpi):
Between 40.0 rockwell c and 45.0 rockwell c Thread Size: 0.312 inches stud thread Surface Finish: 63.0 microinches undercuts Special Features: Unthreaded section dia. 0.3125 inch Material: Steel comp 8740 or steel comp 4140 or steel comp 4340 Material Specification: Ams 6322 assn standard 1st material response or ams 6382 assn standard 2nd material response or ams 6415 assn standard 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qu-p-416, ty2, cl 3 federal specification single treatment response Style Designator: Recessed Thread Series Designator: Uns stud thread Sheft Life: Na	24 nut thread
Thread Size: 0.312 inches stud thread 0.312 inches stud thread Surface Finish: 0.30 microinches undercuts Special Features: Unthreaded section dia. 0.3125 inch Material: Steel comp 8740 or steel comp 4140 or steel comp 4340 Material Specification: Amerial Specification: Amerial Specification: Amerial Specification: Cadmium and chromate Surface Treatment Specification single treatment response Surface Treatment Specification single treatment response Surface Treatment Specification: Recessed Thread Series Designator: Uns stud thread Sheft Life: Na	Hardness Rating:
0.312 inches stud thread Surface Finish: 63.0 microinches undercuts Special Features: Unthreaded section dia. 0.3125 inch Material: Steel comp 8740 or steel comp 4140 or steel comp 4340 Material Specification: Ams 6322 assn standard 1st material response or ams 6382 assn standard 2nd material response or ams 6415 assn standard 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qn-p-416, ty2, cl 3 federal specification single treatment response Style Designator: Recessed Thread Series Designator: Uns stud thread Sheff Life: Na	Between 40.0 rockwell c and 45.0 rockwell c
Surface Finish: 63.0 microinches undercuts Special Features: Unthreaded section dia. 0.3125 inch Material: Steel comp 8740 or steel comp 4140 or steel comp 4340 Material Specification: Arms 6322 assn standard 1st material response or ams 6382 assn standard 2nd material response or ams 6415 assn standard 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl 3 federal specification single treatment response Style Designator: Recessed Thread Series Designator: Uns stud thread Shelf Life: N/a	Thread Size:
63.0 microinches undercuts Special Features: Unthreaded section dia. 0.3125 inch Material: Steel comp 8740 or steel comp 4140 or steel comp 4340 Material Specification: Ams 6322 assn standard 1st material response or ams 6382 assn standard 2nd material response or ams 6415 assn standard 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl 3 federal specification single treatment response Style Designator: Recessed Thread Series Designator: Uns stud thread Shelf Life: N/a	0.312 inches stud thread
Special Features: Unthreaded section dia. 0.3125 inch Material: Steel comp 8740 or steel comp 4140 or steel comp 4340 Material Specification: Ams 6322 assn standard 1st material response or ams 6382 assn standard 2nd material response or ams 6415 assn standard 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl 3 federal specification single treatment response Style Designator: Recessed Thread Series Designator: Uns stud thread Shelf Life: N/a	Surface Finish:
Unthreaded section dia. 0.3125 inch Material: Steel comp 8740 or steel comp 4140 or steel comp 4340 Material Specification: Ams 6322 assn standard 1st material response or ams 6382 assn standard 2nd material response or ams 6415 assn standard 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl 3 federal specification single treatment response Style Designator: Recessed Thread Series Designator: Uns stud thread Shelf Life: N/a	63.0 microinches undercuts
Material: Steel comp 8740 or steel comp 4140 or steel comp 4340 Material Specification: Ams 6322 assn standard 1st material response or ams 6382 assn standard 2nd material response or ams 6415 assn standard 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl 3 federal specification single treatment response Style Designator: Recessed Thread Series Designator: Uns stud thread Shift Life: N/a	Special Features:
Steel comp 8740 or steel comp 4140 or steel comp 4340 Material Specification: Ams 6322 assn standard 1st material response or ams 6382 assn standard 2nd material response or ams 6415 assn standard 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl 3 federal specification single treatment response Style Designator: Recessed Thread Series Designator: Uns stud thread Shelf Life: N/a	Unthreaded section dia. 0.3125 inch
Material Specification: Ams 6322 assn standard 1st material response or ams 6382 assn standard 2nd material response or ams 6415 assn standard 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl 3 federal specification single treatment response Style Designator: Recessed Thread Series Designator: Uns stud thread Shelf Life: N/a	Material:
Ams 6322 assn standard 1st material response or ams 6382 assn standard 2nd material response or ams 6415 assn standard 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl 3 federal specification single treatment response Style Designator: Recessed Thread Series Designator: Uns stud thread Shelf Life: N/a	Steel comp 8740 or steel comp 4140 or steel comp 4340
response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl 3 federal specification single treatment response Style Designator: Recessed Thread Series Designator: Uns stud thread Shelf Life: N/a	Material Specification:
Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl 3 federal specification single treatment response Style Designator: Recessed Thread Series Designator: Uns stud thread Shelf Life: N/a	Ams 6322 assn standard 1st material response or ams 6382 assn standard 2nd material response or ams 6415 assn standard 3rd material
Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl 3 federal specification single treatment response Style Designator: Recessed Thread Series Designator: Uns stud thread Shelf Life: N/a	response
Surface Treatment Specification: Qq-p-416, ty2, cl 3 federal specification single treatment response Style Designator: Recessed Thread Series Designator: Uns stud thread Shelf Life: N/a	Surface Treatment:
Qq-p-416, ty2, cl 3 federal specification single treatment response Style Designator: Recessed Thread Series Designator: Uns stud thread Shelf Life: N/a	Cadmium and chromate
Style Designator: Recessed Thread Series Designator: Uns stud thread Shelf Life: N/a	Surface Treatment Specification:
Recessed Thread Series Designator: Uns stud thread Shelf Life: N/a	Qq-p-416, ty2, cl 3 federal specification single treatment response
Thread Series Designator: Uns stud thread Shelf Life: N/a	Style Designator:
Uns stud thread Shelf Life: N/a	Recessed
Shelf Life: N/a	Thread Series Designator:
N/a	Uns stud thread
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:
 Demilitarization:	 Demilitarization:

No

NSN 5307-01-212-0214

Recessed Stud - Page 2 of 2

Fiig: A051a0

