## NSN 5307-01-216-7916

Stepped Stud - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5307-01-216-7916

| New Online at https://defobasegroup.com/hsi//3007-01 |
|--|
| Thread Class:  |
| 3a nut thread  |
| Thread Pitch Diameters:                              |
| +0.2338 to 0.2353 inches stud thread                 |
| Thread Direction:                                    |
| Right-hand stud thread                               |
| Thread Length:                                       |
| 0.375 inches stud thread                             |
| Shank Diameter:                                      |
| Between 0.164 inches and 0.174 inches                |
| Overall Length:                                      |
| 0.875 inches   |
| Thready Qty Per Inch (tpi):                          |
| 32 nut thread  |
| Hardness Rating:                                     |
| Between 26.0 rockwell c and 32.0 rockwell c          |
| Thread Size:   |
| 0.250 inches stud thread                             |
| Surface Finish:                                      |
| 63.0 microinches shank                               |
| Material:  |
| Steel  |
| Material Specification:                              |
| Ams 6322 assn standard single material response      |
| Surface Treatment:                                   |
| Cadmium  |
| Surface Treatment Specification:                     |
| Ams 2400 assn standard single treatment response     |
| Style Designator:                                    |
| Stepped  |
| Thread Series Designator:                            |
| Uns stud thread                                      |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:                                     |
| -  |
| Demilitarization:                                    |
| No   |
| Fiig:  |
| A051a0   |
|  |