## NSN 5307-01-257-0786

Stepped Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-01-257-0786

**Thread Class:** 3a nut thread **Thread Pitch Diameters:** +0.2930/+0.2945 inches stud thread **Thread Direction:** Right-hand stud thread Thread Length: 0.438 inches nut thread and 0.509 inches nut thread **Shank Diameter:** Between 0.221 inches and 0.231 inches **Overall Length:** Between 1.178 inches and 1.198 inches **Distance From Cotter Pin Hole Centerline To Nut End:** 0.100 inches first hole and 0.120 inches first hole **Cotter Pin Hole Diameter:** 0.065 inches first hole and 0.072 inches first hole **End Application:** Spec item Thready Qty Per Inch (tpi): 28 nut thread Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Thread Size: 0.312 inches stud thread **Surface Finish:** 63.0 microinches shank Material: Steel comp 8740 **Material Specification:** Ams6322 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams2400 assn standard single treatment response **Style Designator:** Stepped **Thread Series Designator:** Uns stud thread Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5307-01-257-0786

Stepped Stud - Page 2 of 2



Demilitarization:

No

Fiig:

A051a0