NSN 5307-01-276-9797

Shouldered Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-01-276-9797

View Online at https://aerobasegroup.com/nsn/5307-01-276-9797
Thread Class:
3a stud thread
Thread Direction:
Right-hand stud thread
Thread Length:
0.325 inches stud thread
Shoulder Diameter:
Between 0.357 inches and 0.377 inches
Shoulder Length:
Between 0.064 inches and 0.074 inches
Overall Length:
Between 1.330 inches and 1.360 inches
Nut End Shank Length:
Between 0.433 inches and 0.443 inches
Thready Qty Per Inch (tpi):
32 stud thread
Thread Size:
0.190 inches stud thread
Criticality Code Justification:
Supp
Stud End Shank Length:
Between 0.183 inches and 0.193 inches
Stud End Shank Diameter:
Between 0.188 inches and 0.190 inches
Surface Finish:
32.0 microinches shank
Nut End Shank Diameter:
Between 0.188 inches and 0.190 inches
Special Features:
0.0791 in. Min 0.0806 in. Maximum inthex. Wrenching accom nut end
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response and ams 4967 assn standard single material response
Style Designator:
Shouldered
Supplementary Features:
Shank diameter close tol 0.1885 in. Min 0.1895 in. Max; 5380.0 lb min dbl shear; 3180.0 lb min tension rating
Thread Series Designator:
Unjf stud thread
Specification Data:

73197-hl146 manufacturers standard

NSN 5307-01-276-9797

Shouldered Stud - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A051a0

