## NSN 5307-01-283-9262

Welding Stud - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5307-01-283-9262

| view Online at https://aerobasegroup.com/hsn/5307-01-263-9262 |  |
|---|--|
| Thread Class:   |  |
| 2a nut thread   |  |
| Thread Direction:   |  |
| Right-hand nut thread   |  |
| Thread Length:  |  |
| 0.750 inches  |  |
| Shoulder Diameter:  |  |
| Between 0.625 inches and 0.687 inches                         |  |
| Shoulder Length:  |  |
| Between 0.093 inches and 0.125 inches                         |  |
| Unthreaded End Diameter:                                      |  |
| Between 0.325 inches and 0.335 inches                         |  |
| Unthreaded End Length:  |  |
| Between 4.094 inches and 4.188 inches                         |  |
| Length Excluding Fluxed Welding Tip:                          |  |
| Between 4.969 inches and 5.031 inches                         |  |
| Features Provided:  |  |
| Heat shield   |  |
| Thready Qty Per Inch (tpi):                                   |  |
| 2a nut thread   |  |
| Thread Size:  |  |
| 0.375 inches nut thread                                       |  |
| Special Features:   |  |
| Furnished with arc shield made of heat resistant ceramic      |  |
| Material:   |  |
| Steel   |  |
| Style Designator:   |  |
| Welding   |  |
| Thread Series Designator:                                     |  |
| Unc nut thread  |  |
| Specification Or Standard:                                    |  |
| 2 type and 4 class  |  |
| Shelf Life:   |  |
| N/a   |  |
| Unit Of Measure:  |  |
|   |  |
| Demilitarization:   |  |
| No  |  |
| Fiig:   |  |
| A051a0  |  |
| Mil-std (military Standard):                                  |  |
| Mil-s-24149 spec  |  |

Mil-s-24149 spec.