## NSN 5307-01-345-6708

Shouldered Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-01-345-6708

### Thread Class:

3a nut thread3a stud thread

#### **Thread Direction:**

Right-hand nut threadright-hand stud thread

### Thread Length:

0.253 inches nut thread and 0.273 inches nut thread0.253 inches stud thread and 0.273 inches stud thread

#### Shoulder Diameter:

Between 0.357 inches and 0.377 inches

#### Shoulder Length:

Between 0.064 inches and 0.074 inches

#### **Overall Length:**

0.843 inches

#### Nut End Shank Length:

Between 0.057 inches and 0.067 inches

#### Thready Qty Per Inch (tpi):

32 nut thread32 stud thread

#### Thread Size:

0.190 inches nut thread0.190 inches stud thread

#### Stud End Shank Length:

Between 0.057 inches and 0.067 inches

#### Stud End Shank Diameter:

Between 0.1885 inches and 0.1895 inches

#### Surface Finish:

32.0 microinches shank

#### Nut End Shank Diameter:

Between 0.1885 inches and 0.1895 inches

#### Special Features:

Cetyl alcohol lube per hi-shear specification 305; socket drive both ends

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

#### Style Designator:

Shouldered

#### Thread Series Designator:

Unjf nut threadunjf stud thread

#### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# **NSN 5307-01-345-6708** Shouldered Stud - Page 2 of 2

Fiig: A051a0

